




# MBA

## Socket Set Screws - Brass Tipped



Brass tipped grub screws. Helps to prevent shaft damage on harder shafts.

### Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-610RS	2.184mm (2-56 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.79 <i>0.031</i>		304 Stainless Steel (18-8)	Socket	0.454 mm / 56 TPI
# BTS-615RS	2.184mm (2-56 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	0.79 <i>0.031</i>		304 Stainless Steel (18-8)	Socket	0.454 mm / 56 TPI
# BTS-10RS	2.845mm (4-40 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.00 <i>0.000</i>		Black Oxide Steel	Socket	0.635 mm / 40 TPI
# BTS-15RS	2.845mm (4-40 UNC)	4.8 <i>0.189</i>	5.6 <i>0.220</i>	1.59 <i>0.063</i>		Black Oxide Steel	Socket	0.635 mm / 40 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-630RS	2.845mm (4-40 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.59 <i>0.063</i>		304 Stainless Steel (18-8)	Socket	0.635 mm / 40 TPI
# BTS-25RS	3.5mm (6-32 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.59 <i>0.063</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-30RS	3.5mm (6-32 UNC)	4.8 <i>0.189</i>	5.6 <i>0.220</i>	1.59 <i>0.063</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-35RS	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.59 <i>0.063</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-40RS	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	10.3 <i>0.406</i>	1.59 <i>0.063</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-1210RS	4.0mm (M4x0.7 Standard)	4.0 <i>0.157</i>	5.2 <i>0.205</i>	2.4 <i>0.094</i>		Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
# SSBTM040x0060SKT-3	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	6.5 <i>0.256</i>	2.5 <i>0.098</i>	2.50 <i>0.098</i>	303 Stainless	Socket	0.700 mm / 36.29 TPI
SSBTM040x0060SKT-B	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	6.5 <i>0.256</i>	2.5 <i>0.098</i>	2.50 <i>0.098</i>	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
# BTS-1215RS	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	7.2 <i>0.283</i>	2.4 <i>0.094</i>		Black Oxide Steel	Socket	0.700 mm / 36.29 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM040x0080SKT-B	4.0mm (M4x0.7 Standard)	8.0	8.5	2.5	2.50	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
		<i>0.315</i>	<i>0.335</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0080SKT-3	4.0mm (M4x0.7 Standard)	8.0	8.5	2.5	2.50	303 Stainless	Socket	0.700 mm / 36.29 TPI
		<i>0.315</i>	<i>0.335</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0100SKT-B	4.0mm (M4x0.7 Standard)	10.0	10.5	2.5	2.50	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
		<i>0.394</i>	<i>0.413</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0100SKT-3	4.0mm (M4x0.7 Standard)	10.0	10.5	2.5	2.50	303 Stainless	Socket	0.700 mm / 36.29 TPI
		<i>0.394</i>	<i>0.413</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0120SKT-3	4.0mm (M4x0.7 Standard)	12.0	12.5	2.5	2.50	303 Stainless	Socket	0.700 mm / 36.29 TPI
		<i>0.472</i>	<i>0.492</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0120SKT-B	4.0mm (M4x0.7 Standard)	12.0	12.5	2.5	2.50	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
		<i>0.472</i>	<i>0.492</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0160SKT-3	4.0mm (M4x0.7 Standard)	16.0	16.5	2.5	2.50	303 Stainless	Socket	0.700 mm / 36.29 TPI
		<i>0.630</i>	<i>0.650</i>	<i>0.098</i>	<i>0.098</i>			
# SSBTM040x0160SKT-B	4.0mm (M4x0.7 Standard)	16.0	16.5	2.5	2.50	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
		<i>0.630</i>	<i>0.650</i>	<i>0.098</i>	<i>0.098</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM040x0200SKT-B	4.0mm (M4x0.7 Standard)	20.0 <i>0.787</i>	20.5 <i>0.807</i>	2.5 <i>0.098</i>	2.50 <i>0.098</i>	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
# BTS-45RS	4.166mm (8-32 UNC)	3.2 <i>0.126</i>	4.4 <i>0.173</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-50RS	4.166mm (8-32 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-55RS	4.166mm (8-32 UNC)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-60RS	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-65RS	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-70RS	4.762mm (10-24 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	1.058 mm / 24 TPI
# BTS-90RS	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	1.058 mm / 24 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-695RS	4.762mm (10-32 UNF)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38 <i>0.094</i>		304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-95RS	4.762mm (10-32 UNF)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38 <i>0.094</i>		304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-700RS	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38 <i>0.094</i>		304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-100RS	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-110RS	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-710RS	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38 <i>0.094</i>		304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-115RS	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	20.2 <i>0.795</i>	2.38 <i>0.094</i>		Black Oxide Steel	Socket	0.794 mm / 32 TPI
# SSBTM050x0080SKT-B	5.0mm (M5x0.8)	8.0 <i>0.315</i>	8.5 <i>0.335</i>	3.0 <i>0.118</i>	3.00 <i>0.118</i>	Black Oxide Steel	Socket	0.800 mm / 31.75 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM050x0080SKT-3	5.0mm (M5x0.8)	8.0	8.5	3.0	3.00	303 Stainless	Socket	0.800 mm / 31.75 TPI
		<i>0.315</i>	<i>0.335</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0100SKT-3	5.0mm (M5x0.8)	10.0	10.5	3.0	3.00	303 Stainless	Socket	0.800 mm / 31.75 TPI
		<i>0.394</i>	<i>0.413</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0100SKT-B	5.0mm (M5x0.8)	10.0	10.5	3.0	3.00	Black Oxide Steel	Socket	0.800 mm / 31.75 TPI
		<i>0.394</i>	<i>0.413</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0120SKT-3	5.0mm (M5x0.8)	12.0	12.5	3.0	3.00	303 Stainless	Socket	0.800 mm / 31.75 TPI
		<i>0.472</i>	<i>0.492</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0120SKT-B	5.0mm (M5x0.8)	12.0	12.5	3.0	3.00	Black Oxide Steel	Socket	0.800 mm / 31.75 TPI
		<i>0.472</i>	<i>0.492</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0160SKT-3	5.0mm (M5x0.8)	16.0	16.5	3.0	3.00	303 Stainless	Socket	0.800 mm / 31.75 TPI
		<i>0.630</i>	<i>0.650</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0160SKT-B	5.0mm (M5x0.8)	16.0	16.5	3.0	3.00	Black Oxide Steel	Socket	0.800 mm / 31.75 TPI
		<i>0.630</i>	<i>0.650</i>	<i>0.118</i>	<i>0.118</i>			
# SSBTM050x0200SKT-3	5.0mm (M5x0.8)	20.0	20.5	3.0	3.00	303 Stainless	Socket	0.800 mm / 31.75 TPI
		<i>0.787</i>	<i>0.807</i>	<i>0.118</i>	<i>0.118</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM050x0200SKT-B	5.0mm (M5x0.8)	20.0 <i>0.787</i>	20.5 <i>0.807</i>	3.0 <i>0.118</i>	3.00 <i>0.118</i>	Black Oxide Steel	Socket	0.800 mm / 31.75 TPI
# SSBTM050x0250SKT-B	5.0mm (M5x0.8)	25.0 <i>0.984</i>	25.5 <i>1.004</i>	3.0 <i>0.118</i>	3.00 <i>0.118</i>	Black Oxide Steel	Socket	0.800 mm / 31.75 TPI
# BTS-1230RS	6.0mm (M6x1 Standard)	6.0 <i>0.236</i>	7.6 <i>0.299</i>	3.2 <i>0.126</i>		Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# BTS-1235RS	6.0mm (M6x1 Standard)	8.0 <i>0.315</i>	9.6 <i>0.378</i>	3.2 <i>0.126</i>		Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0100SKT-3	6.0mm (M6x1 Standard)	10.0 <i>0.394</i>	11.0 <i>0.433</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	303 Stainless	Socket	1.000 mm / 25.4 TPI
SSBTM060x0100SKT-B	6.0mm (M6x1 Standard)	10.0 <i>0.394</i>	11.0 <i>0.433</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# BTS-1240RS	6.0mm (M6x1 Standard)	10.0 <i>0.394</i>	11.6 <i>0.457</i>	3.2 <i>0.126</i>		Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0120SKT-B	6.0mm (M6x1 Standard)	12.0 <i>0.472</i>	13.0 <i>0.512</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM060x0120SKT-3	6.0mm (M6x1 Standard)	12.0 <i>0.472</i>	13.0 <i>0.512</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	303 Stainless	Socket	1.000 mm / 25.4 TPI
# BTS-1245RS	6.0mm (M6x1 Standard)	12.0 <i>0.472</i>	13.6 <i>0.535</i>	3.2 <i>0.126</i>		Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0160SKT-B	6.0mm (M6x1 Standard)	16.0 <i>0.630</i>	17.0 <i>0.669</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0160SKT-3	6.0mm (M6x1 Standard)	16.0 <i>0.630</i>	17.0 <i>0.669</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	303 Stainless	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0200SKT-3	6.0mm (M6x1 Standard)	20.0 <i>0.787</i>	21.0 <i>0.827</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	303 Stainless	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0200SKT-B	6.0mm (M6x1 Standard)	20.0 <i>0.787</i>	21.0 <i>0.827</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0250SKT-3	6.0mm (M6x1 Standard)	25.0 <i>0.984</i>	26.0 <i>1.024</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	303 Stainless	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0250SKT-B	6.0mm (M6x1 Standard)	25.0 <i>0.984</i>	26.0 <i>1.024</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM060x0320SKT-B	6.0mm (M6x1 Standard)	32.0 <i>1.260</i>	33.0 <i>1.299</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0320SKT-3	6.0mm (M6x1 Standard)	32.0 <i>1.260</i>	33.0 <i>1.299</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	303 Stainless	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0400SKT-B	6.0mm (M6x1 Standard)	40.0 <i>1.575</i>	41.0 <i>1.614</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# SSBTM060x0500SKT-B	6.0mm (M6x1 Standard)	50.0 <i>1.969</i>	51.0 <i>2.008</i>	4.0 <i>0.157</i>	4.00 <i>0.157</i>	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
# BTS-120RS	6.35mm (1/4-20 UNC)	4.8 <i>0.189</i>	6.3 <i>0.248</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-160RS	6.35mm (1/4-28 UNF)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	0.907 mm / 28 TPI
# BTS-125RS	6.35mm (1/4-20 UNC)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-130RS	6.35mm (1/4-20 UNC)	7.9 <i>0.311</i>	9.5 <i>0.374</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-725RS	6.35mm (1/4-20 UNC)	7.9 <i>0.311</i>	9.5 <i>0.374</i>	3.18 <i>0.125</i>		304 Stainless Steel (18-8)	Socket	1.270 mm / 20 TPI
# BTS-165RS	6.35mm (1/4-28 UNF)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	0.907 mm / 28 TPI
# BTS-135RS	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-730RS	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18 <i>0.125</i>		304 Stainless Steel (18-8)	Socket	1.270 mm / 20 TPI
# BTS-170RS	6.35mm (1/4-28 UNF)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	0.907 mm / 28 TPI
# BTS-140RS	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-735RS	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.18 <i>0.125</i>		304 Stainless Steel (18-8)	Socket	1.270 mm / 20 TPI
# BTS-145RS	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	17.5 <i>0.689</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-150RS	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	20.6 <i>0.811</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-155RS	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	27.0 <i>1.063</i>	3.18 <i>0.125</i>		Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-175RS	7.938mm (5/16-18 UNC)	6.4 <i>0.252</i>	8.7 <i>0.343</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-180RS	7.938mm (5/16-18 UNC)	7.9 <i>0.311</i>	10.3 <i>0.406</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-185RS	7.938mm (5/16-18 UNC)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-190RS	7.938mm (5/16-18 UNC)	12.7 <i>0.500</i>	15.1 <i>0.594</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-195RS	7.938mm (5/16-18 UNC)	15.9 <i>0.626</i>	18.3 <i>0.720</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-200RS	7.938mm (5/16-18 UNC)	19.1 <i>0.752</i>	21.4 <i>0.843</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-205RS	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-780RS	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.76 <i>0.187</i>		304 Stainless Steel (18-8)	Socket	1.411 mm / 18 TPI
# BTS-210RS	7.938mm (5/16-24 UNF)	6.4 <i>0.252</i>	8.7 <i>0.343</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.058 mm / 24 TPI
# BTS-785RS	7.938mm (5/16-24 UNF)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76 <i>0.187</i>		304 Stainless Steel (18-8)	Socket	1.058 mm / 24 TPI
# BTS-1250RS	8.0mm (M8x1.25 Standard)	8.0 <i>0.315</i>	10.4 <i>0.409</i>	0.00 <i>0.000</i>		Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
SSBTM080x0120SKT-B	8.0mm (M8x1.25 Standard)	12.0 <i>0.472</i>	13.5 <i>0.531</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0120SKT-3	8.0mm (M8x1.25 Standard)	12.0 <i>0.472</i>	13.5 <i>0.531</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	303 Stainless	Socket	1.250 mm / 20.32 TPI
# BTS-1260RS	8.0mm (M8x1.25 Standard)	12.0 <i>0.472</i>	14.4 <i>0.567</i>	4.8 <i>0.189</i>		Black Oxide Steel	Socket	1.250 mm / 20.32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM080x0160SKT-B	8.0mm (M8x1.25 Standard)	16.0 <i>0.630</i>	17.5 <i>0.689</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0160SKT-3	8.0mm (M8x1.25 Standard)	16.0 <i>0.630</i>	17.5 <i>0.689</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	303 Stainless	Socket	1.250 mm / 20.32 TPI
# BTS-1265RS	8.0mm (M8x1.25 Standard)	16.0 <i>0.630</i>	18.4 <i>0.724</i>	4.8 <i>0.189</i>		Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0200SKT-B	8.0mm (M8x1.25 Standard)	20.0 <i>0.787</i>	21.5 <i>0.846</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0200SKT-3	8.0mm (M8x1.25 Standard)	20.0 <i>0.787</i>	21.5 <i>0.846</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	303 Stainless	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0250SKT-3	8.0mm (M8x1.25 Standard)	25.0 <i>0.984</i>	26.5 <i>1.043</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	303 Stainless	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0250SKT-B	8.0mm (M8x1.25 Standard)	25.0 <i>0.984</i>	26.5 <i>1.043</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0320SKT-B	8.0mm (M8x1.25 Standard)	32.0 <i>1.260</i>	33.5 <i>1.319</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM080x0320SKT-3	8.0mm (M8x1.25 Standard)	32.0 <i>1.260</i>	33.5 <i>1.319</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	303 Stainless	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0400SKT-B	8.0mm (M8x1.25 Standard)	40.0 <i>1.575</i>	41.5 <i>1.634</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0400SKT-3	8.0mm (M8x1.25 Standard)	40.0 <i>1.575</i>	41.5 <i>1.634</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	303 Stainless	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0500SKT-B	8.0mm (M8x1.25 Standard)	50.0 <i>1.969</i>	51.5 <i>2.028</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSBTM080x0630SKT-B	8.0mm (M8x1.25 Standard)	63.0 <i>2.480</i>	64.5 <i>2.539</i>	6.0 <i>0.236</i>	6.00 <i>0.236</i>	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# BTS-235RS	9.525mm (3/8-16 UNC)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.588 mm / 16 TPI
# BTS-240RS	9.525mm (3/8-16 UNC)	12.7 <i>0.500</i>	15.1 <i>0.594</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.588 mm / 16 TPI
# BTS-250RS	9.525mm (3/8-16 UNC)	19.1 <i>0.752</i>	21.4 <i>0.843</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.588 mm / 16 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# BTS-810RS	9.525mm (3/8-16 UNC)	19.1 <i>0.752</i>	21.4 <i>0.843</i>	4.76 <i>0.187</i>		304 Stainless Steel (18-8)	Socket	1.588 mm / 16 TPI
# BTS-255RS	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.588 mm / 16 TPI
# BTS-260RS	9.525mm (3/8-24 UNF)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.058 mm / 24 TPI
# BTS-265RS	9.525mm (3/8-24 UNF)	12.7 <i>0.500</i>	15.1 <i>0.594</i>	4.76 <i>0.187</i>		Black Oxide Steel	Socket	1.058 mm / 24 TPI
# BTS-1270RS	10.0mm (M10x1.5)	10.0 <i>0.394</i>	12.4 <i>0.488</i>	4.8 <i>0.189</i>		Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
# BTS-1275RS	10.0mm (M10x1.5)	12.0 <i>0.472</i>	14.4 <i>0.567</i>	4.8 <i>0.189</i>		Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0160SKT-3	10.0mm (M10x1.5)	16.0 <i>0.630</i>	18.0 <i>0.709</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	303 Stainless	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0160SKT-B	10.0mm (M10x1.5)	16.0 <i>0.630</i>	18.0 <i>0.709</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM100x0200SKT-B	10.0mm (M10x1.5)	20.0 <i>0.787</i>	22.0 <i>0.866</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0200SKT-3	10.0mm (M10x1.5)	20.0 <i>0.787</i>	22.0 <i>0.866</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	303 Stainless	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0250SKT-B	10.0mm (M10x1.5)	25.0 <i>0.984</i>	27.0 <i>1.063</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0250SKT-3	10.0mm (M10x1.5)	25.0 <i>0.984</i>	27.0 <i>1.063</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	303 Stainless	Socket	1.500 mm / 16.93 TPI
# BTS-1285RS	10.0mm (M10x1.5)	25.0 <i>0.984</i>	27.4 <i>1.079</i>	4.8 <i>0.189</i>		Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0320SKT-3	10.0mm (M10x1.5)	32.0 <i>1.260</i>	34.0 <i>1.339</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	303 Stainless	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0320SKT-B	10.0mm (M10x1.5)	32.0 <i>1.260</i>	34.0 <i>1.339</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
# SSBTM100x0400SKT-3	10.0mm (M10x1.5)	40.0 <i>1.575</i>	42.0 <i>1.654</i>	8.0 <i>0.315</i>	8.00 <i>0.315</i>	303 Stainless	Socket	1.500 mm / 16.93 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM100x0400SKT-B	10.0mm (M10x1.5)	40.0	42.0	8.0	8.00	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
		<i>1.575</i>	<i>1.654</i>	<i>0.315</i>	<i>0.315</i>			
# SSBTM100x0500SKT-3	10.0mm (M10x1.5)	50.0	52.0	8.0	8.00	303 Stainless	Socket	1.500 mm / 16.93 TPI
		<i>1.969</i>	<i>2.047</i>	<i>0.315</i>	<i>0.315</i>			
# SSBTM100x0500SKT-B	10.0mm (M10x1.5)	50.0	52.0	8.0	8.00	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
		<i>1.969</i>	<i>2.047</i>	<i>0.315</i>	<i>0.315</i>			
# SSBTM100x0630SKT-B	10.0mm (M10x1.5)	63.0	65.0	8.0	8.00	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
		<i>2.480</i>	<i>2.559</i>	<i>0.315</i>	<i>0.315</i>			
# SSBTM100x0800SKT-B	10.0mm (M10x1.5)	80.0	82.0	8.0	8.00	Black Oxide Steel	Socket	1.500 mm / 16.93 TPI
		<i>3.150</i>	<i>3.228</i>	<i>0.315</i>	<i>0.315</i>			
# SSBTM120x0200SKT-B	12.0mm (M12x1.75 Standard)	20.0	22.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>0.787</i>	<i>0.866</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0200SKT-3	12.0mm (M12x1.75 Standard)	20.0	22.0	10.0	10.00	303 Stainless	Socket	1.750 mm / 14.51 TPI
		<i>0.787</i>	<i>0.866</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0250SKT-3	12.0mm (M12x1.75 Standard)	25.0	27.0	10.0	10.00	303 Stainless	Socket	1.750 mm / 14.51 TPI
		<i>0.984</i>	<i>1.063</i>	<i>0.394</i>	<i>0.394</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM120x0250SKT-B	12.0mm (M12x1.75 Standard)	25.0	27.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>0.984</i>	<i>1.063</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0320SKT-B	12.0mm (M12x1.75 Standard)	32.0	34.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>1.260</i>	<i>1.339</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0320SKT-3	12.0mm (M12x1.75 Standard)	32.0	34.0	10.0	10.00	303 Stainless	Socket	1.750 mm / 14.51 TPI
		<i>1.260</i>	<i>1.339</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0400SKT-B	12.0mm (M12x1.75 Standard)	40.0	42.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>1.575</i>	<i>1.654</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0400SKT-3	12.0mm (M12x1.75 Standard)	40.0	42.0	10.0	10.00	303 Stainless	Socket	1.750 mm / 14.51 TPI
		<i>1.575</i>	<i>1.654</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0500SKT-B	12.0mm (M12x1.75 Standard)	50.0	52.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>1.969</i>	<i>2.047</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0500SKT-3	12.0mm (M12x1.75 Standard)	50.0	52.0	10.0	10.00	303 Stainless	Socket	1.750 mm / 14.51 TPI
		<i>1.969</i>	<i>2.047</i>	<i>0.394</i>	<i>0.394</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Brass Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSBTM120x0630SKT-3	12.0mm (M12x1.75 Standard)	63.0	65.0	10.0	10.00	303 Stainless	Socket	1.750 mm / 14.51 TPI
		<i>2.480</i>	<i>2.559</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0630SKT-B	12.0mm (M12x1.75 Standard)	63.0	65.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>2.480</i>	<i>2.559</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x0800SKT-B	12.0mm (M12x1.75 Standard)	80.0	82.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>3.150</i>	<i>3.228</i>	<i>0.394</i>	<i>0.394</i>			
# SSBTM120x1000SKT-B	12.0mm (M12x1.75 Standard)	100.0	102.0	10.0	10.00	Black Oxide Steel	Socket	1.750 mm / 14.51 TPI
		<i>3.937</i>	<i>4.016</i>	<i>0.394</i>	<i>0.394</i>			
# BTS-275RS	12.7mm (1/2-13 UNC)	12.7	15.9	6.35		Black Oxide Steel	Socket	1.954 mm / 13 TPI
		<i>0.500</i>	<i>0.626</i>	<i>0.250</i>				
# BTS-285RS	12.7mm (1/2-13 UNC)	19.1	22.2	6.35		Black Oxide Steel	Socket	1.954 mm / 13 TPI
		<i>0.752</i>	<i>0.874</i>	<i>0.250</i>				
# BTS-290RS	12.7mm (1/2-13 UNC)	25.4	28.6	6.35		Black Oxide Steel	Socket	1.954 mm / 13 TPI
		<i>1.000</i>	<i>1.126</i>	<i>0.250</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)
