




# MBA

## Socket Set Screws - Flat Tip



Flat tip grub screws

### Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSF632Cx0032SKT-B	3.5mm (6-32 UNC)	3.2  <i>0.126</i>	Hardened Steel, Black Oxide Finish	1.59  <i>0.063</i>	Flat Tip	0.794 mm / 32 TPI
# SSF632Cx0048SKT-B	3.5mm (6-32 UNC)	4.8  <i>0.189</i>	Hardened Steel, Black Oxide Finish	1.59  <i>0.063</i>	Flat Tip	0.794 mm / 32 TPI
# SSF632Cx0064SKT-B	3.5mm (6-32 UNC)	6.4  <i>0.252</i>	Hardened Steel, Black Oxide Finish	1.59  <i>0.063</i>	Flat Tip	0.794 mm / 32 TPI
# SSF632Cx0079SKT-B	3.5mm (6-32 UNC)	7.9  <i>0.311</i>	Hardened Steel, Black Oxide Finish	1.59  <i>0.063</i>	Flat Tip	0.794 mm / 32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSF632Cx0095SKT-B	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	Hardened Steel, Black Oxide Finish	1.59 <i>0.063</i>	Flat Tip	0.794 mm / 32 TPI
SSFM040x0040SKT-B	4.0mm (M4x0.7 Standard)	4.0 <i>0.157</i>	Hardened Steel, Black Oxide Finish	2.00 <i>0.079</i>	Cup Point	0.700 mm / 36.29 TPI
# SSFM040x0050SKT-B	4.0mm (M4x0.7 Standard)	5.0 <i>0.197</i>	Hardened Steel, Black Oxide Finish	2.00 <i>0.079</i>	Cup Point	0.700 mm / 36.29 TPI
SSFM040x0060SKT-B	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	Hardened Steel, Black Oxide Finish	2.00 <i>0.079</i>	Cup Point	0.700 mm / 36.29 TPI
SSFM040x0080SKT-B	4.0mm (M4x0.7 Standard)	8.0 <i>0.315</i>	Hardened Steel, Black Oxide Finish	2.00 <i>0.079</i>	Cup Point	0.700 mm / 36.29 TPI
# SSFM040x0100SKT-B	4.0mm (M4x0.7 Standard)	10.0 <i>0.394</i>	Hardened Steel, Black Oxide Finish	2.00 <i>0.079</i>	Cup Point	0.700 mm / 36.29 TPI
# SSFM040x0120SKT-B	4.0mm (M4x0.7 Standard)	12.0 <i>0.472</i>	Hardened Steel, Black Oxide Finish	2.00 <i>0.079</i>	Flat Tip	0.700 mm / 36.29 TPI
SSFM040x0160SKT-B	4.0mm (M4x0.7 Standard)	16.0 <i>0.630</i>	Hardened Steel, Black Oxide Finish	2.0 <i>0.079</i>	Cup Point	0.700 mm / 36.29 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSF832Cx0032SKT-B	4.166mm (8-32 UNC)	3.2  <i>0.126</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF832Cx0048SKT-B	4.166mm (8-32 UNC)	4.8  <i>0.189</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF832Cx0064SKT-B	4.166mm (8-32 UNC)	6.4  <i>0.252</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF832Cx0079SKT-B	4.166mm (8-32 UNC)	7.9  <i>0.311</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF832Cx0095SKT-B	4.166mm (8-32 UNC)	9.5  <i>0.374</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF832Cx0127SKT-B	4.166mm (8-32 UNC)	12.7  <i>0.500</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF832Cx0159SKT-B	4.166mm (8-32 UNC)	15.9  <i>0.626</i>	Hardened Steel, Black Oxide Finish	1.98  <i>0.078</i>	Flat Tip	0.794 mm / 32 TPI
# SSF1024Cx0048SKT-B	4.762mm (10-24 UNC)	4.8  <i>0.189</i>	Hardened Steel, Black Oxide Finish	2.38  <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSF1024Cx0064SKT-B	4.762mm (10-24 UNC)	6.4 <i>0.252</i>	Hardened Steel, Black Oxide Finish	2.38 <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI
# SSF1024Cx0079SKT-B	4.762mm (10-24 UNC)	7.9 <i>0.311</i>	Hardened Steel, Black Oxide Finish	2.38 <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI
# SSF1024Cx0095SKT-B	4.762mm (10-24 UNC)	9.5 <i>0.374</i>	Hardened Steel, Black Oxide Finish	2.38 <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI
# SSF1024Cx0127SKT-B	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	Hardened Steel, Black Oxide Finish	2.38 <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI
# SSF1024Cx0159SKT-B	4.762mm (10-24 UNC)	15.9 <i>0.626</i>	Hardened Steel, Black Oxide Finish	2.38 <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI
# SSF1024Cx0191SKT-B	4.762mm (10-24 UNC)	19.1 <i>0.752</i>	Hardened Steel, Black Oxide Finish	2.38 <i>0.094</i>	Flat Tip	1.058 mm / 24 TPI
SSFM050x0050SKT-B	5.0mm (M5x0.8)	5.0 <i>0.197</i>	Hardened Steel, Black Oxide Finish	2.50 <i>0.098</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0060SKT-B	5.0mm (M5x0.8)	6.0 <i>0.236</i>	Hardened Steel, Black Oxide Finish	2.50 <i>0.098</i>	Cup Point	0.800 mm / 31.75 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM050x0080SKT-B	5.0mm (M5x0.8)	8.0 <i>0.315</i>	Hardened Steel, Black Oxide Finish	2.50 <i>0.098</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0100SKT-B	5.0mm (M5x0.8)	10.0 <i>0.394</i>	Hardened Steel, Black Oxide Finish	2.50 <i>0.098</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0120SKT-B	5.0mm (M5x0.8)	12.0 <i>0.472</i>	Hardened Steel, Black Oxide Finish	2.50 <i>0.098</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0160SKT-B	5.0mm (M5x0.8)	16.0 <i>0.630</i>	Hardened Steel, Black Oxide Finish	2.0 <i>0.079</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0200SKT-B	5.0mm (M5x0.8)	20.0 <i>0.787</i>	Hardened Steel, Black Oxide Finish	2.0 <i>0.079</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0250SKT-B	5.0mm (M5x0.8)	25.0 <i>0.984</i>	Hardened Steel, Black Oxide Finish	2.0 <i>0.079</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0300SKT-B	5.0mm (M5x0.8)	30.0 <i>1.181</i>	Hardened Steel, Black Oxide Finish	2.0 <i>0.079</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM050x0350SKT-B	5.0mm (M5x0.8)	35.0 <i>1.378</i>	Hardened Steel, Black Oxide Finish	2.0 <i>0.079</i>	Cup Point	0.800 mm / 31.75 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM050x0400SKT-B	5.0mm (M5x0.8)	40.0  <i>1.575</i>	Hardened Steel, Black Oxide Finish	2.0  <i>0.079</i>	Cup Point	0.800 mm / 31.75 TPI
# SSFM060x0060SKT-B	6.0mm (M6x1 Standard)	6.0  <i>0.236</i>	Hardened Steel, Black Oxide Finish	3.00  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSFM060x0080SKT-B	6.0mm (M6x1 Standard)	8.0  <i>0.315</i>	Hardened Steel, Black Oxide Finish	3.00  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSFM060x0100SKT-B	6.0mm (M6x1 Standard)	10.0  <i>0.394</i>	Hardened Steel, Black Oxide Finish	3.00  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSFM060x0120SKT-B	6.0mm (M6x1 Standard)	12.0  <i>0.472</i>	Hardened Steel, Black Oxide Finish	3.00  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSFM060x0160SKT-B	6.0mm (M6x1 Standard)	16.0  <i>0.630</i>	Hardened Steel, Black Oxide Finish	3.00  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSFM060x0200SKT-B	6.0mm (M6x1 Standard)	20.0  <i>0.787</i>	Hardened Steel, Black Oxide Finish	3.0  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSFM060x0250SKT-B	6.0mm (M6x1 Standard)	25.0  <i>0.984</i>	Hardened Steel, Black Oxide Finish	3.0  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM060x0350SKT-B	6.0mm (M6x1 Standard)	35.0  <i>1.378</i>	Hardened Steel, Black Oxide Finish	3.0  <i>0.118</i>	Cup Point	1.000 mm / 25.4 TPI
# SSF14Cx0064SKT-B	6.35mm (1/4-20 UNC)	6.4  <i>0.252</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI
# SSF14Cx0079SKT-B	6.35mm (1/4-20 UNC)	7.9  <i>0.311</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI
# SSF14Cx0095SKT-B	6.35mm (1/4-20 UNC)	9.5  <i>0.374</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI
# SSF14Cx0127SKT-B	6.35mm (1/4-20 UNC)	12.7  <i>0.500</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI
# SSF14Cx0159SKT-B	6.35mm (1/4-20 UNC)	15.9  <i>0.626</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI
# SSF14Cx0191SKT-B	6.35mm (1/4-20 UNC)	19.1  <i>0.752</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI
# SSF14Cx0254SKT-B	6.35mm (1/4-20 UNC)	25.4  <i>1.000</i>	Hardened Steel, Black Oxide Finish	3.18  <i>0.125</i>	Flat Tip	1.270 mm / 20 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time  
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd  
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSF516Cx0079SKT-B	7.938mm (5/16-18 UNC)	7.9  <i>0.311</i>	Hardened Steel, Black Oxide Finish	3.97  <i>0.156</i>	Flat Tip	1.411 mm / 18 TPI
# SSF516Cx0095SKT-B	7.938mm (5/16-18 UNC)	9.5  <i>0.374</i>	Hardened Steel, Black Oxide Finish	3.97  <i>0.156</i>	Flat Tip	1.411 mm / 18 TPI
# SSF516Cx0127SKT-B	7.938mm (5/16-18 UNC)	12.7  <i>0.500</i>	Hardened Steel, Black Oxide Finish	3.97  <i>0.156</i>	Flat Tip	1.411 mm / 18 TPI
# SSF516Cx0159SKT-B	7.938mm (5/16-18 UNC)	15.9  <i>0.626</i>	Hardened Steel, Black Oxide Finish	3.97  <i>0.156</i>	Flat Tip	1.411 mm / 18 TPI
# SSF516Cx0191SKT-B	7.938mm (5/16-18 UNC)	19.1  <i>0.752</i>	Hardened Steel, Black Oxide Finish	3.97  <i>0.156</i>	Flat Tip	1.411 mm / 18 TPI
# SSF516Cx0254SKT-B	7.938mm (5/16-18 UNC)	25.4  <i>1.000</i>	Hardened Steel, Black Oxide Finish	3.97  <i>0.156</i>	Flat Tip	1.411 mm / 18 TPI
# SSFM080x0080SKT-B	8.0mm (M8x1.25 Standard)	8.0  <i>0.315</i>	Hardened Steel, Black Oxide Finish	4.00  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSFM080x0100SKT-B	8.0mm (M8x1.25 Standard)	10.0  <i>0.394</i>	Hardened Steel, Black Oxide Finish	4.00  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM080x0120SKT-B	8.0mm (M8x1.25 Standard)	12.0  <i>0.472</i>	Hardened Steel, Black Oxide Finish	4.00  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSFM080x0160SKT-B	8.0mm (M8x1.25 Standard)	16.0  <i>0.630</i>	Hardened Steel, Black Oxide Finish	4.00  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSFM080x0200SKT-B	8.0mm (M8x1.25 Standard)	20.0  <i>0.787</i>	Hardened Steel, Black Oxide Finish	4.00  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSFM080x0250SKT-B	8.0mm (M8x1.25 Standard)	25.0  <i>0.984</i>	Hardened Steel, Black Oxide Finish	4.0  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSFM080x0300SKT-B	8.0mm (M8x1.25 Standard)	30.0  <i>1.181</i>	Hardened Steel, Black Oxide Finish	4.0  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSFM080x0350SKT-B	8.0mm (M8x1.25 Standard)	35.0  <i>1.378</i>	Hardened Steel, Black Oxide Finish	4.0  <i>0.157</i>	Cup Point	1.250 mm / 20.32 TPI
# SSF38Cx0079SKT-B	9.525mm (3/8-16 UNC)	7.9  <i>0.311</i>	Hardened Steel, Black Oxide Finish	4.8  <i>0.189</i>	Cup Point	1.588 mm / 16 TPI
# SSF38Cx0095SKT-B	9.525mm (3/8-16 UNC)	9.5  <i>0.374</i>	Hardened Steel, Black Oxide Finish	4.8  <i>0.189</i>	Cup Point	1.588 mm / 16 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSF38Cx0127SKT-B	9.525mm (3/8-16 UNC)	12.7 <i>0.500</i>	Hardened Steel, Black Oxide Finish	4.8 <i>0.189</i>	Cup Point	1.588 mm / 16 TPI
# SSF38Cx0159SKT-B	9.525mm (3/8-16 UNC)	15.9 <i>0.626</i>	Hardened Steel, Black Oxide Finish	4.8 <i>0.189</i>	Cup Point	1.588 mm / 16 TPI
# SSF38Cx0191SKT-B	9.525mm (3/8-16 UNC)	19.1 <i>0.752</i>	Hardened Steel, Black Oxide Finish	4.8 <i>0.189</i>	Cup Point	1.588 mm / 16 TPI
# SSF38Cx0254SKT-B	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	Hardened Steel, Black Oxide Finish	4.8 <i>0.189</i>	Cup Point	1.588 mm / 16 TPI
# SSFM100x0100SKT-B	10.0mm (M10x1.5)	10.0 <i>0.394</i>	Hardened Steel, Black Oxide Finish	5.0 <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM100x0120SKT-B	10.0mm (M10x1.5)	12.0 <i>0.472</i>	Hardened Steel, Black Oxide Finish	5.0 <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM100x0160SKT-B	10.0mm (M10x1.5)	16.0 <i>0.630</i>	Hardened Steel, Black Oxide Finish	5.0 <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM100x0200SKT-B	10.0mm (M10x1.5)	20.0 <i>0.787</i>	Hardened Steel, Black Oxide Finish	5.0 <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM100x0250SKT-B	10.0mm (M10x1.5)	25.0  <i>0.984</i>	Hardened Steel, Black Oxide Finish	5.0  <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM100x0300SKT-B	10.0mm (M10x1.5)	30.0  <i>1.181</i>	Hardened Steel, Black Oxide Finish	5.0  <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM100x0350SKT-B	10.0mm (M10x1.5)	35.0  <i>1.378</i>	Hardened Steel, Black Oxide Finish	5.0  <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM100x0400SKT-B	10.0mm (M10x1.5)	40.0  <i>1.575</i>	Hardened Steel, Black Oxide Finish	5.0  <i>0.197</i>	Cup Point	1.500 mm / 16.93 TPI
# SSFM120x0120SKT-B	12.0mm (M12x1.75 Standard)	12.0  <i>0.472</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM120x0160SKT-B	12.0mm (M12x1.75 Standard)	16.0  <i>0.630</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM120x0200SKT-B	12.0mm (M12x1.75 Standard)	20.0  <i>0.787</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM120x0250SKT-B	12.0mm (M12x1.75 Standard)	25.0  <i>0.984</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM120x0300SKT-B	12.0mm (M12x1.75 Standard)	30.0  <i>1.181</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM120x0350SKT-B	12.0mm (M12x1.75 Standard)	35.0  <i>1.378</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM120x0400SKT-B	12.0mm (M12x1.75 Standard)	40.0  <i>1.575</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM120x0450SKT-B	12.0mm (M12x1.75 Standard)	45.0  <i>1.772</i>	Hardened Steel, Black Oxide Finish	6.0  <i>0.236</i>	Cup Point	1.750 mm / 14.51 TPI
# SSFM030x0030SKTB	3.0mm (M3x0.5 Standard)	3.0  <i>0.118</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0040SKTB	3.0mm (M3x0.5 Standard)	4.0  <i>0.157</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0050SKTB	3.0mm (M3x0.5 Standard)	5.0  <i>0.197</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0060SKTB	3.0mm (M3x0.5 Standard)	6.0  <i>0.236</i>	Hardened Steel, Black Oxide Finish			

# Indicates item not stocked at time of printing - Please enquire for lead time  
E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd  
MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Flat Tip

Part Number	Major Thread Diameter mm  <i>inches</i>	Thread Length (L) mm  <i>inches</i>	Material	Hex Key Size mm  <i>inches</i>	Type	Pitch in mm / Threads Per Inch mm / No.
# SSFM030x0080SKTB	3.0mm (M3x0.5 Standard)	8.0  <i>0.315</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0100SKTB	3.0mm (M3x0.5 Standard)	10.0  <i>0.394</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0120SKTB	3.0mm (M3x0.5 Standard)	12.0  <i>0.472</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0160SKTB	3.0mm (M3x0.5 Standard)	16.0  <i>0.630</i>	Hardened Steel, Black Oxide Finish			
# SSFM040x0200SKTB	4.0mm (M4x0.7 Standard)	20.0  <i>0.787</i>	Hardened Steel, Black Oxide Finish			
# SSFM030x0200SKTB	3.0mm (M3x0.5 Standard)	20.0  <i>0.787</i>	Hardened Steel, Black Oxide Finish			
# SSFM040x0250SKTB	4.0mm (M4x0.7 Standard)	25.0  <i>0.984</i>	Hardened Steel, Black Oxide Finish			
# SSFM040x0300SKTB	4.0mm (M4x0.7 Standard)	30.0  <i>1.181</i>	Hardened Steel, Black Oxide Finish			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

**Socket Set Screws - Flat Tip**

Part Number	Major Thread Diameter mm	Thread Length (L) mm	Material	Hex Key Size mm	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>		
# SSFM060x0300SKTB	6.0mm (M6x1 Standard)	30.0				1.181



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)
