




# MBA

## Socket Set Screws - Nylon Tipped



Nylon tipped grub screws. Soft tip compresses into threads to become self locking. Helps to prevent shaft damage.

### Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# NTM2-4	2.0mm (M2x0.4 Standard)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	Stainless Steel	Socket	0.400 mm / 63.5 TPI
SSNTM020x0032SKT-416	2.0mm (M2x0.4 Standard)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	416 Stainless	Socket	0.400 mm / 63.5 TPI
# NTM2-5	2.0mm (M2x0.4 Standard)	4.2 <i>0.165</i>	5.0 <i>0.197</i>	0.8	Stainless Steel	Socket	0.400 mm / 63.5 TPI
# SSNTM020x0042SKT-416	2.0mm (M2x0.4 Standard)	4.2 <i>0.165</i>	5.0 <i>0.197</i>	0.8	416 Stainless	Socket	0.400 mm / 63.5 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time  
E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd  
MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (Tl) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# SSNTM020x0052SKT-416	2.0mm (M2x0.4 Standard)	5.2 <i>0.205</i>	6.0 <i>0.236</i>	0.8	416 Stainless	Socket	0.400 mm / 63.5 TPI
SSNTM020x0062SKT-416	2.0mm (M2x0.4 Standard)	6.2 <i>0.244</i>	7.0 <i>0.276</i>	0.8	416 Stainless	Socket	0.400 mm / 63.5 TPI
# BTS-910RS	2.184mm (2-56 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.79	304 Stainless Steel (18-8)	Socket	0.454 mm / 56 TPI
# SSNT256Cx0032SKT-416	2.184mm (2-56 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	416 Stainless	Socket	0.454 mm / 56 TPI
# SSNT256Cx0032SL-416	2.184mm (2-56 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	416 Stainless	Slotted	0.454 mm / 56 TPI
# BTS-915RS	2.184mm (2-56 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	0.79	304 Stainless Steel (18-8)	Socket	0.454 mm / 56 TPI
# BTS-920RS	2.845mm (4-40 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.59	304 Stainless Steel (18-8)	Socket	0.635 mm / 40 TPI
# BTS-310RS	2.845mm (4-40 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.59	Black Oxide Steel	Socket	0.635 mm / 40 TPI
# SSNT440Cx0032SKT-416	2.845mm (4-40 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	416 Stainless	Socket	0.635 mm / 40 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# SSNT440Cx0032SL-416	2.845mm (4-40 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	416 Stainless	Slotted	0.635 mm / 40 TPI
# BTS-315RS	2.845mm (4-40 UNC)	4.8 <i>0.189</i>	5.6 <i>0.220</i>	1.59	Black Oxide Steel	Socket	0.635 mm / 40 TPI
BTS-320RS	2.845mm (4-40 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.59	Black Oxide Steel	Socket	0.635 mm / 40 TPI
# BTS-930RS	2.845mm (4-40 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.59	304 Stainless Steel (18-8)	Socket	0.635 mm / 40 TPI
# BTS-1410RS	3.0mm (M3x0.5 Standard)	3.0 <i>0.118</i>	3.8 <i>0.150</i>	1.6	304 Stainless Steel (18-8)	Socket	0.500 mm / 50.8 TPI
SSNTM030x0032SKT-416	3.0mm (M3x0.5 Standard)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	416 Stainless	Socket	0.500 mm / 50.8 TPI
# BTS-1415RS	3.0mm (M3x0.5 Standard)	4.0 <i>0.157</i>	4.8 <i>0.189</i>	1.6	304 Stainless Steel (18-8)	Socket	0.500 mm / 50.8 TPI
SSNTM030x0042SL-416	3.0mm (M3x0.5 Standard)	4.2 <i>0.165</i>	5.0 <i>0.197</i>	1.6	416 Stainless	Slotted	0.500 mm / 50.8 TPI
SSNTM030x0042SKT-416	3.0mm (M3x0.5 Standard)	4.2 <i>0.165</i>	5.0 <i>0.197</i>	1.6	416 Stainless	Socket	0.500 mm / 50.8 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-1420RS	3.0mm (M3x0.5 Standard)	5.0 <i>0.197</i>	5.8 <i>0.228</i>	1.6	304 Stainless Steel (18-8)	Socket	0.500 mm / 50.8 TPI
SSNTM030x0052SKT-416	3.0mm (M3x0.5 Standard)	5.2 <i>0.205</i>	6.0 <i>0.236</i>	1.6	416 Stainless	Socket	0.500 mm / 50.8 TPI
SSNTM030x0062SKT-416	3.0mm (M3x0.5 Standard)	6.2 <i>0.244</i>	7.0 <i>0.276</i>	1.6	416 Stainless	Socket	0.500 mm / 50.8 TPI
# BTS-325RS	3.5mm (6-32 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.59	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-935RS	3.5mm (6-32 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.59	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# SSNT632Cx0032SL-416	3.5mm (6-32 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	416 Stainless	Slotted	0.794 mm / 32 TPI
# SSNT632Cx0032SKT-416	3.5mm (6-32 UNC)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	416 Stainless	Socket	0.794 mm / 32 TPI
# BTS-330RS	3.5mm (6-32 UNC)	4.8 <i>0.189</i>	5.6 <i>0.220</i>	1.59	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-940RS	3.5mm (6-32 UNC)	4.8 <i>0.189</i>	5.6 <i>0.220</i>	1.59	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-335RS	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.59	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-945RS	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.59	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
SSNT632Cx0064SKT-416	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.6	416 Stainless	Socket	0.794 mm / 32 TPI
# BTS-340RS	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	10.3 <i>0.406</i>	1.59	Black Oxide Steel	Socket	0.794 mm / 32 TPI
SSNTM040x0038SKT-416	4.0mm (M4x0.7 Standard)	3.8 <i>0.150</i>	5.0 <i>0.197</i>	2.4	416 Stainless	Socket	0.700 mm / 36.29 TPI
# BTS-1425RS	4.0mm (M4x0.7 Standard)	4.0 <i>0.157</i>	5.2 <i>0.205</i>	2.4	304 Stainless Steel (18-8)	Socket	0.700 mm / 36.29 TPI
# BTS-1310RS	4.0mm (M4x0.7 Standard)	4.0 <i>0.157</i>	5.2 <i>0.205</i>	2.4	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
SSNTM040x0058SKT-416	4.0mm (M4x0.7 Standard)	5.8 <i>0.228</i>	7.0 <i>0.276</i>	2.4	416 Stainless	Socket	0.700 mm / 36.29 TPI
# SSNTM040x0058SL-416	4.0mm (M4x0.7 Standard)	5.8 <i>0.228</i>	7.0 <i>0.276</i>	2.4	416 Stainless	Slotted	0.700 mm / 36.29 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-1315RS	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	7.2 <i>0.283</i>	2.4	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
# BTS-1430RS	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	7.2 <i>0.283</i>	2.4	304 Stainless Steel (18-8)	Socket	0.700 mm / 36.29 TPI
# BTS-1320RS	4.0mm (M4x0.7 Standard)	8.0 <i>0.315</i>	9.2 <i>0.362</i>	2.4	Black Oxide Steel	Socket	0.700 mm / 36.29 TPI
# SSNTM040x0098SKT-416	4.0mm (M4x0.7 Standard)	9.8 <i>0.386</i>	11.0 <i>0.433</i>	2.4	416 Stainless	Socket	0.700 mm / 36.29 TPI
# BTS-1435RS	4.0mm (M4x0.7 Standard)	10.0 <i>0.394</i>	11.2 <i>0.441</i>	2.4	304 Stainless Steel (18-8)	Socket	0.700 mm / 36.29 TPI
# SSNTM040x0138SKT-416	4.0mm (M4x0.7 Standard)	13.8 <i>0.543</i>	15.0 <i>0.591</i>	2.4	416 Stainless	Socket	0.700 mm / 36.29 TPI
# BTS-950RS	4.166mm (8-32 UNC)	3.2 <i>0.126</i>	4.4 <i>0.173</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-345RS	4.166mm (8-32 UNC)	3.2 <i>0.126</i>	4.4 <i>0.173</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-955RS	4.166mm (8-32 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-350RS	4.166mm (8-32 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# SSNT832Cx0048SKT-416	4.166mm (8-32 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	416 Stainless	Socket	0.794 mm / 32 TPI
# SSNT832Cx0048SL-416	4.166mm (8-32 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	416 Stainless	Slotted	0.794 mm / 32 TPI
# BTS-355RS	4.166mm (8-32 UNC)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-960RS	4.166mm (8-32 UNC)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# SSNT832Cx0095SKT-416	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.4	416 Stainless	Socket	0.794 mm / 32 TPI
# BTS-360RS	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-965RS	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-365RS	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-970RS	4.762mm (10-24 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38	304 Stainless Steel (18-8)	Socket	1.058 mm / 24 TPI
# SSNT1024Cx0048SKT-416	4.762mm (10-24 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	416 Stainless	Socket	1.058 mm / 24 TPI
# SSNT1024Cx0048SL-416	4.762mm (10-24 UNC)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	416 Stainless	Slotted	1.058 mm / 24 TPI
# BTS-375RS	4.762mm (10-24 UNC)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38	Black Oxide Steel	Socket	1.058 mm / 24 TPI
# SSNT1024Cx0095SKT-416	4.762mm (10-24 UNC)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.4	416 Stainless	Socket	1.058 mm / 24 TPI
# BTS-395RS	4.762mm (10-32 UNF)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-995RS	4.762mm (10-32 UNF)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
SSNT1032Fx0048SKT-416	4.762mm (10-32 UNF)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	416 Stainless	Socket	0.794 mm / 32 TPI
# SSNT1032Fx0048SL-416	4.762mm (10-32 UNF)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	416 Stainless	Slotted	0.794 mm / 32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-400RS	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-1000RS	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# SSNT1032Fx0095SKT-416	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.4	416 Stainless	Socket	0.794 mm / 32 TPI
# BTS-405RS	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-105RS	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-1005RS	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-1010RS	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
# BTS-410RS	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI
# BTS-415RS	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	20.2 <i>0.795</i>	2.38	Black Oxide Steel	Socket	0.794 mm / 32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-1015RS	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	20.2 <i>0.795</i>	2.38	304 Stainless Steel (18-8)	Socket	0.794 mm / 32 TPI
SSNTM050x0058SKT-416	5.0mm (M5x0.8)	5.8 <i>0.228</i>	7.0 <i>0.276</i>	2.4	416 Stainless	Socket	0.800 mm / 31.75 TPI
# BTS-1440RS	5.0mm (M5x0.8)	6.0 <i>0.236</i>	7.2 <i>0.283</i>	2.4	304 Stainless Steel (18-8)	Socket	0.800 mm / 31.75 TPI
SSNTM050x0098SKT-416	5.0mm (M5x0.8)	9.8 <i>0.386</i>	11.0 <i>0.433</i>	2.4	416 Stainless	Socket	0.800 mm / 31.75 TPI
# SSNTM050x0098SL-416	5.0mm (M5x0.8)	9.8 <i>0.386</i>	11.0 <i>0.433</i>	2.4	416 Stainless	Slotted	0.800 mm / 31.75 TPI
# BTS-1445RS	5.0mm (M5x0.8)	10.0 <i>0.394</i>	11.2 <i>0.441</i>	2.4	304 Stainless Steel (18-8)	Socket	0.800 mm / 31.75 TPI
# SSNTM050x0138SKT-416	5.0mm (M5x0.8)	13.8 <i>0.543</i>	15.0 <i>0.591</i>	2.4	416 Stainless	Socket	0.800 mm / 31.75 TPI
# SSNTM050x0198SKT-416	5.0mm (M5x0.8)	19.8 <i>0.780</i>	21.0 <i>0.827</i>	2.4	416 Stainless	Socket	0.800 mm / 31.75 TPI
# SSNTM060x0059SL-416	6.0mm (M6x1 Standard)	5.9 <i>0.232</i>	7.5 <i>0.295</i>	3.2	416 Stainless	Slotted	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (Tl) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
SSNTM060x0059SKT-416	6.0mm (M6x1 Standard)	5.9 <i>0.232</i>	7.5 <i>0.295</i>	3.2	416 Stainless	Socket	1.000 mm / 25.4 TPI
# BTS-1450RS	6.0mm (M6x1 Standard)	6.0 <i>0.236</i>	7.6 <i>0.299</i>	3.2	304 Stainless Steel (18-8)	Socket	1.000 mm / 25.4 TPI
# BTS-1335RS	6.0mm (M6x1 Standard)	8.0 <i>0.315</i>	9.6 <i>0.378</i>	3.2	Black Oxide Steel	Socket	1.000 mm / 25.4 TPI
SSNTM060x0099SKT-416	6.0mm (M6x1 Standard)	9.9 <i>0.390</i>	11.5 <i>0.453</i>	3.2	416 Stainless	Socket	1.000 mm / 25.4 TPI
# SSNTM060x0099SL-416	6.0mm (M6x1 Standard)	9.9 <i>0.390</i>	11.5 <i>0.453</i>	3.2	416 Stainless	Slotted	1.000 mm / 25.4 TPI
# SSNTM060x0159SKT-416	6.0mm (M6x1 Standard)	15.9 <i>0.626</i>	17.5 <i>0.689</i>	3.2	416 Stainless	Socket	1.000 mm / 25.4 TPI
# SSNTM060x0249SKT-416	6.0mm (M6x1 Standard)	24.9 <i>0.980</i>	26.5 <i>1.043</i>	3.2	416 Stainless	Socket	1.000 mm / 25.4 TPI
# SSNTM060x0249SL-416	6.0mm (M6x1 Standard)	24.9 <i>0.980</i>	26.5 <i>1.043</i>	3.2	416 Stainless	Slotted	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-420RS	6.35mm (1/4-20 UNC)	4.8 <i>0.189</i>	6.3 <i>0.248</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-425RS	6.35mm (1/4-20 UNC)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-460RS	6.35mm (1/4-28 UNF)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.18	Black Oxide Steel	Socket	0.907 mm / 28 TPI
# BTS-1020RS	6.35mm (1/4-20 UNC)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.18	304 Stainless Steel (18-8)	Socket	1.270 mm / 20 TPI
# SSNT14Cx0064SKT-416	6.35mm (1/4-20 UNC)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.2	416 Stainless	Socket	1.270 mm / 20 TPI
# SSNT14Cx0064SL-416	6.35mm (1/4-20 UNC)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.2	416 Stainless	Slotted	1.270 mm / 20 TPI
# BTS-430RS	6.35mm (1/4-20 UNC)	7.9 <i>0.311</i>	9.5 <i>0.374</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# SSNT14Cx0095SKT-416	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.2	416 Stainless	Socket	1.270 mm / 20 TPI
# BTS-465RS	6.35mm (1/4-28 UNF)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18	Black Oxide Steel	Socket	0.907 mm / 28 TPI
# BTS-1045RS	6.35mm (1/4-28 UNF)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18	304 Stainless Steel (18-8)	Socket	0.907 mm / 28 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-1030RS	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18	304 Stainless Steel (18-8)	Socket	1.270 mm / 20 TPI
# BTS-435RS	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-470RS	6.35mm (1/4-28 UNF)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.18	Black Oxide Steel	Socket	0.907 mm / 28 TPI
# BTS-1035RS	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.18	304 Stainless Steel (18-8)	Socket	1.270 mm / 20 TPI
# BTS-440RS	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-445RS	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	17.5 <i>0.689</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-450RS	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	20.6 <i>0.811</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-455RS	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	27.0 <i>1.063</i>	3.18	Black Oxide Steel	Socket	1.270 mm / 20 TPI
# BTS-1065RS	7.938mm (5/16-18 UNC)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76	304 Stainless Steel (18-8)	Socket	1.411 mm / 18 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TL) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-485RS	7.938mm (5/16-18 UNC)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76	Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-490RS	7.938mm (5/16-18 UNC)	12.7 <i>0.500</i>	15.1 <i>0.594</i>	4.76	Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-500RS	7.938mm (5/16-18 UNC)	19.1 <i>0.752</i>	21.4 <i>0.843</i>	4.76	Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-505RS	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.76	Black Oxide Steel	Socket	1.411 mm / 18 TPI
# BTS-1350RS	8.0mm (M8x1.25 Standard)	8.0 <i>0.315</i>	10.4 <i>0.409</i>	0.00	Black Oxide Steel	Socket	1.250 mm / 20.32 TPI
# SSNTM080x0099SKT-416	8.0mm (M8x1.25 Standard)	9.9 <i>0.390</i>	11.5 <i>0.453</i>	3.2	416 Stainless	Socket	1.250 mm / 20.32 TPI
# SSNTM080x0159SKT-416	8.0mm (M8x1.25 Standard)	15.9 <i>0.626</i>	17.5 <i>0.689</i>	3.2	416 Stainless	Socket	1.250 mm / 20.32 TPI
# SSNTM080x0249SKT-416	8.0mm (M8x1.25 Standard)	24.9 <i>0.980</i>	26.5 <i>1.043</i>	3.2	416 Stainless	Socket	1.250 mm / 20.32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Nylon Tipped

Part Number	Major Thread Diameter mm	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Head Style	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>				
# BTS-535RS	9.525mm (3/8-16 UNC)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.76	Black Oxide Steel	Socket	1.588 mm / 16 TPI
# BTS-540RS	9.525mm (3/8-16 UNC)	12.7 <i>0.500</i>	15.1 <i>0.594</i>	4.76	Black Oxide Steel	Socket	1.588 mm / 16 TPI
# BTS-1115RS	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.76	304 Stainless Steel (18-8)	Socket	1.588 mm / 16 TPI
# BTS-555RS	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.76	Black Oxide Steel	Socket	1.588 mm / 16 TPI
# SSNTM100x0121SKT-416	10.0mm (M10x1.5)	12.1 <i>0.476</i>	14.5 <i>0.571</i>	4.8	416 Stainless	Socket	1.500 mm / 16.93 TPI
# SSNTM100x0201SKT-416	10.0mm (M10x1.5)	20.1 <i>0.791</i>	22.5 <i>0.886</i>	4.8	416 Stainless	Socket	1.500 mm / 16.93 TPI
# SSNTM100x0301SKT-416	10.0mm (M10x1.5)	30.1 <i>1.185</i>	32.5 <i>1.280</i>	4.8	416 Stainless	Socket	1.500 mm / 16.93 TPI
# BTS-585RS	12.7mm (1/2-13 UNC)	19.1 <i>0.752</i>	22.2 <i>0.874</i>	6.35	Black Oxide Steel	Socket	1.954 mm / 13 TPI
# BTS-590RS	12.7mm (1/2-13 UNC)	25.4 <i>1.000</i>	28.6 <i>1.126</i>	6.35	Black Oxide Steel	Socket	1.954 mm / 13 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

