




MBA

Socket Set Screws - Rolling Ball Tip



Rolling ball tip for locating into a hole

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
SSRBM030x0052SKT-C	3.0mm (M3x0.5 Standard)	5.2 <i>0.205</i>	1.500	1.50 <i>0.059</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.500 mm / 50.8 TPI
# SSRBM030x0052SKT-4	3.0mm (M3x0.5 Standard)	5.2 <i>0.205</i>	1.500	1.50 <i>0.059</i>	304 Stainless	440C St. St., HRC 55...60	None	0.500 mm / 50.8 TPI
SSRBM030x0102SKT-4	3.0mm (M3x0.5 Standard)	10.2 <i>0.402</i>	1.500	1.50 <i>0.059</i>	304 Stainless	440C St. St., HRC 55...60	None	0.500 mm / 50.8 TPI
# SSRBM030x0102SKT-C	3.0mm (M3x0.5 Standard)	10.2 <i>0.402</i>	1.500	1.50 <i>0.059</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.500 mm / 50.8 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
SSRBM040x0065SKT-4	4.0mm (M4x0.7 Standard)	6.5 <i>0.256</i>	2.500	2.00 <i>0.079</i>	304 Stainless	440C St. St., HRC 55...60	None	0.700 mm / 36.29 TPI
# SSRBM040x0065SKT-C	4.0mm (M4x0.7 Standard)	6.5 <i>0.256</i>	2.500	2.00 <i>0.079</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.700 mm / 36.29 TPI
SSRBM040x0105SKT-4	4.0mm (M4x0.7 Standard)	10.5 <i>0.413</i>	2.500	2.00 <i>0.079</i>	304 Stainless	440C St. St., HRC 55...60	None	0.700 mm / 36.29 TPI
# SSRBM040x0105SKT-C	4.0mm (M4x0.7 Standard)	10.5 <i>0.413</i>	2.500	2.00 <i>0.079</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.700 mm / 36.29 TPI
SSRBM040x0165SKT-4	4.0mm (M4x0.7 Standard)	16.5 <i>0.650</i>	2.500	2.00 <i>0.079</i>	304 Stainless	440C St. St., HRC 55...60	None	0.700 mm / 36.29 TPI
# SSRBM040x0165SKT-C	4.0mm (M4x0.7 Standard)	16.5 <i>0.650</i>	2.500	2.00 <i>0.079</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.700 mm / 36.29 TPI
SSRBM050x0086SKT-4	5.0mm (M5x0.8)	8.6 <i>0.339</i>	3.000	2.50 <i>0.098</i>	304 Stainless	440C St. St., HRC 55...60	None	0.800 mm / 31.75 TPI
# SSRBM050x0086SKT-C	5.0mm (M5x0.8)	8.6 <i>0.339</i>	3.000	2.50 <i>0.098</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM050x0126SKT-4	5.0mm (M5x0.8)	12.6 <i>0.496</i>	3.000	2.50 <i>0.098</i>	304 Stainless	440C St. St., HRC 55...60	None	0.800 mm / 31.75 TPI
# SSRBM050x0126SKT-C	5.0mm (M5x0.8)	12.6 <i>0.496</i>	3.000	2.50 <i>0.098</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.800 mm / 31.75 TPI
# SSRBM050x0206SKT-4	5.0mm (M5x0.8)	20.6 <i>0.811</i>	3.000	2.50 <i>0.098</i>	304 Stainless	440C St. St., HRC 55...60	None	0.800 mm / 31.75 TPI
# SSRBM050x0206SKT-C	5.0mm (M5x0.8)	20.6 <i>0.811</i>	3.000	2.50 <i>0.098</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	0.800 mm / 31.75 TPI
SSRBM060x0108SKT-C	6.0mm (M6x1 Standard)	10.8 <i>0.425</i>	4.000	3.00 <i>0.118</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.000 mm / 25.4 TPI
# SSRBM060x0108SKT-4	6.0mm (M6x1 Standard)	10.8 <i>0.425</i>	4.000	3.00 <i>0.118</i>	304 Stainless	440C St. St., HRC 55...60	None	1.000 mm / 25.4 TPI
SSRBM060x0168SKT-4	6.0mm (M6x1 Standard)	16.8 <i>0.661</i>	4.000	3.00 <i>0.118</i>	304 Stainless	440C St. St., HRC 55...60	None	1.000 mm / 25.4 TPI
# SSRBM060x0168SKT-C	6.0mm (M6x1 Standard)	16.8 <i>0.661</i>	4.000	3.00 <i>0.118</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM060x0208SKT-4	6.0mm (M6x1 Standard)	20.8 <i>0.819</i>	4.000	3.00 <i>0.118</i>	304 Stainless	440C St. St., HRC 55...60	None	1.000 mm / 25.4 TPI
SSRBM060x0208SKT-C	6.0mm (M6x1 Standard)	20.8 <i>0.819</i>	4.000	3.00 <i>0.118</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.000 mm / 25.4 TPI
# SSRBM060x0258SKT-4	6.0mm (M6x1 Standard)	25.8 <i>1.016</i>	4.000	3.00 <i>0.118</i>	304 Stainless	440C St. St., HRC 55...60	None	1.000 mm / 25.4 TPI
# SSRBM060x0258SKT-C	6.0mm (M6x1 Standard)	25.8 <i>1.016</i>	4.000	3.00 <i>0.118</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.000 mm / 25.4 TPI
# SSRBM080x0112SKT-4	8.0mm (M8x1.25 Standard)	11.2 <i>0.441</i>	5.500	4.00 <i>0.157</i>	304 Stainless	440C St. St., HRC 55...60	None	1.250 mm / 20.32 TPI
# SSRBM080x0112SKT-C	8.0mm (M8x1.25 Standard)	11.2 <i>0.441</i>	5.500	4.00 <i>0.157</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.250 mm / 20.32 TPI
# SSRBM080x0132SKT-4	8.0mm (M8x1.25 Standard)	13.2 <i>0.520</i>	5.500	4.00 <i>0.157</i>	304 Stainless	440C St. St., HRC 55...60	None	1.250 mm / 20.32 TPI
# SSRBM080x0132SKT-C	8.0mm (M8x1.25 Standard)	13.2 <i>0.520</i>	5.500	4.00 <i>0.157</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM080x0212SKT-4	8.0mm (M8x1.25 Standard)	21.2 <i>0.835</i>	5.500	4.00 <i>0.157</i>	304 Stainless	440C St. St., HRC 55...60	None	1.250 mm / 20.32 TPI
# SSRBM080x0212SKT-C	8.0mm (M8x1.25 Standard)	21.2 <i>0.835</i>	5.500	4.00 <i>0.157</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.250 mm / 20.32 TPI
# SSRBM080x0262SKT-C	8.0mm (M8x1.25 Standard)	26.2 <i>1.031</i>	5.500	4.00 <i>0.157</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.250 mm / 20.32 TPI
SSRBM080x0262SKT-4	8.0mm (M8x1.25 Standard)	26.2 <i>1.031</i>	5.500	4.00 <i>0.157</i>	304 Stainless	440C St. St., HRC 55...60	None	1.250 mm / 20.32 TPI
# SSRBM080x0312SKT-4	8.0mm (M8x1.25 Standard)	31.2 <i>1.228</i>	5.500	4.00 <i>0.157</i>	304 Stainless	440C St. St., HRC 55...60	None	1.250 mm / 20.32 TPI
# SSRBM080x0312SKT-C	8.0mm (M8x1.25 Standard)	31.2 <i>1.228</i>	5.500	4.00 <i>0.157</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.250 mm / 20.32 TPI
# SSRBM100x0137SKT-4	10.0mm (M10x1.5)	13.7 <i>0.539</i>	7.000	5.00 <i>0.197</i>	304 Stainless	440C St. St., HRC 55...60	None	1.500 mm / 16.93 TPI
# SSRBM100x0137SKT-C	10.0mm (M10x1.5)	13.7 <i>0.539</i>	7.000	5.00 <i>0.197</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM100x0177SKT-4	10.0mm (M10x1.5)	17.7 <i>0.697</i>	7.000	5.00 <i>0.197</i>	304 Stainless	440C St. St., HRC 55...60	None	1.500 mm / 16.93 TPI
# SSRBM100x0177SKT-C	10.0mm (M10x1.5)	17.7 <i>0.697</i>	7.000	5.00 <i>0.197</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.500 mm / 16.93 TPI
# SSRBM100x0217SKT-4	10.0mm (M10x1.5)	21.7 <i>0.854</i>	7.000	5.00 <i>0.197</i>	304 Stainless	440C St. St., HRC 55...60	None	1.500 mm / 16.93 TPI
SSRBM100x0217SKT-C	10.0mm (M10x1.5)	21.7 <i>0.854</i>	7.000	5.00 <i>0.197</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.500 mm / 16.93 TPI
# SSRBM100x0267SKT-4	10.0mm (M10x1.5)	26.7 <i>1.051</i>	7.000	5.00 <i>0.197</i>	304 Stainless	440C St. St., HRC 55...60	None	1.500 mm / 16.93 TPI
# SSRBM100x0267SKT-C	10.0mm (M10x1.5)	26.7 <i>1.051</i>	7.000	5.00 <i>0.197</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.500 mm / 16.93 TPI
# SSRBM100x0367SKT-4	10.0mm (M10x1.5)	36.7 <i>1.445</i>	7.000	5.00 <i>0.197</i>	304 Stainless	440C St. St., HRC 55...60	None	1.500 mm / 16.93 TPI
# SSRBM100x0367SKT-C	10.0mm (M10x1.5)	36.7 <i>1.445</i>	7.000	5.00 <i>0.197</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM120x0180SKT-4	12.0mm (M12x1.75 Standard)	18.0 <i>0.709</i>	8.500	6.00 <i>0.236</i>	304 Stainless	440C St. St., HRC 55...60	None	1.750 mm / 14.51 TPI
# SSRBM120x0180SKT-C	12.0mm (M12x1.75 Standard)	18.0 <i>0.709</i>	8.500	6.00 <i>0.236</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.750 mm / 14.51 TPI
# SSRBM120x0220SKT-C	12.0mm (M12x1.75 Standard)	22.0 <i>0.866</i>	8.500	6.00 <i>0.236</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.750 mm / 14.51 TPI
# SSRBM120x0220SKT-4	12.0mm (M12x1.75 Standard)	22.0 <i>0.866</i>	8.500	6.00 <i>0.236</i>	304 Stainless	440C St. St., HRC 55...60	None	1.750 mm / 14.51 TPI
# SSRBM120x0320SKT-4	12.0mm (M12x1.75 Standard)	32.0 <i>1.260</i>	8.500	6.00 <i>0.236</i>	304 Stainless	440C St. St., HRC 55...60	None	1.750 mm / 14.51 TPI
# SSRBM120x0320SKT-C	12.0mm (M12x1.75 Standard)	32.0 <i>1.260</i>	8.500	6.00 <i>0.236</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.750 mm / 14.51 TPI
# SSRBM120x0420SKT-4	12.0mm (M12x1.75 Standard)	42.0 <i>1.654</i>	8.500	6.00 <i>0.236</i>	304 Stainless	440C St. St., HRC 55...60	None	1.750 mm / 14.51 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM120x0420SKT-C	12.0mm (M12x1.75 Standard)	42.0 <i>1.654</i>	8.500	6.00 <i>0.236</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	1.750 mm / 14.51 TPI
# SSRBM160x0233SKT-4	16.0mm (M16x2 Standard)	23.3 <i>0.917</i>	12.000	8.00 <i>0.315</i>	304 Stainless	440C St. St., HRC 55...60	None	2.000 mm / 12.7 TPI
# SSRBM160x0233SKT-C	16.0mm (M16x2 Standard)	23.3 <i>0.917</i>	12.000	8.00 <i>0.315</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	2.000 mm / 12.7 TPI
# SSRBM160x0283SKT-4	16.0mm (M16x2 Standard)	28.3 <i>1.114</i>	12.000	8.00 <i>0.315</i>	304 Stainless	440C St. St., HRC 55...60	None	2.000 mm / 12.7 TPI
# SSRBM160x0283SKT-C	16.0mm (M16x2 Standard)	28.3 <i>1.114</i>	12.000	8.00 <i>0.315</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	2.000 mm / 12.7 TPI
# SSRBM160x0383SKT-4	16.0mm (M16x2 Standard)	38.3 <i>1.508</i>	12.000	8.00 <i>0.315</i>	304 Stainless	440C St. St., HRC 55...60	None	2.000 mm / 12.7 TPI
# SSRBM160x0383SKT-C	16.0mm (M16x2 Standard)	38.3 <i>1.508</i>	12.000	8.00 <i>0.315</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	2.000 mm / 12.7 TPI
# SSRBM160x0533SKT-C	16.0mm (M16x2 Standard)	53.3 <i>2.098</i>	12.000	8.00 <i>0.315</i>	Carbon Steel	Carbon Steel, HRC 55...60	Black Oxide	2.000 mm / 12.7 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Rolling Ball Tip

Part Number	Major Thread Diameter mm	Overall Length (L) mm	Ball Diameter (D)	Hex Key Size (s) mm	Body material	Ball material	Finish	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>		<i>inches</i>				
# SSRBM160x0533SKT-4	16.0mm (M16x2 Standard)	53.3	12.000	8.00	304 Stainless	440C St. St., HRC 55..60	None	2.000 mm / 12.7 TPI
		<i>2.098</i>		<i>0.315</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
