




MBA

Utilitrak Guide Rails



Use with Carriage Assemblies - Utilitrak

Guide Rails only.

Use with Carriage Assemblies found in category Carriage Assemblies - Utilitrak

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK1-RL-0120-AL	1	120	30	18.0	60	5.5	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0	Pan Head M5
		<i>4.724</i>	<i>1.181</i>	<i>0.709</i>	<i>2.362</i>	<i>0.217</i>			<i>0.236</i>	
# UTRK1-RL-0190-420	1	190	40	17.5	100	6.9	Aluminum - Clear Anodised	420 Stainless Steel	5.9	Pan Head M6
		<i>7.480</i>	<i>1.575</i>	<i>0.689</i>	<i>3.937</i>	<i>0.272</i>			<i>0.232</i>	
# UTRK1-RL-0190-CS	1	190	40	17.5	100	6.9	Aluminum - Clear Anodised	1045 Carbon Steel	5.9	Pan Head M6
		<i>7.480</i>	<i>1.575</i>	<i>0.689</i>	<i>3.937</i>	<i>0.272</i>			<i>0.232</i>	

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK1-RL-0240-AL	1	240 <i>9.449</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK1-RL-0290-420	1	290 <i>11.417</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0290-CS	1	290 <i>11.417</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0360-AL	1	360 <i>14.173</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK1-RL-0390-420	1	390 <i>15.354</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0390-CS	1	390 <i>15.354</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0490-CS	1	490 <i>19.291</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0490-420	1	490 <i>19.291</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK1-RL-0540-AL	1	540 <i>21.260</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK1-RL-0590-420	1	590 <i>23.228</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0590-CS	1	590 <i>23.228</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0690-420	1	690 <i>27.165</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0690-CS	1	690 <i>27.165</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0720-AL	1	720 <i>28.346</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK1-RL-0790-CS	1	790 <i>31.102</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0790-420	1	790 <i>31.102</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK1-RL-0890-420	1	890 <i>35.039</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0890-CS	1	890 <i>35.039</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0960-AL	1	960 <i>37.795</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK1-RL-0990-420	1	990 <i>38.976</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-0990-CS	1	990 <i>38.976</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-1090-420	1	1090 <i>42.913</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	420 Stainless Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-1090-CS	1	1090 <i>42.913</i>	40 <i>1.575</i>	17.5 <i>0.689</i>	100 <i>3.937</i>	6.9 <i>0.272</i>	Aluminum - Clear Anodised	1045 Carbon Steel	5.9 <i>0.232</i>	Pan Head M6
# UTRK1-RL-1200-AL	1	1200 <i>47.244</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK1-RL-1440-AL	1	1440 <i>56.693</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK1-RL-1800-AL	1	1800 <i>70.866</i>	30 <i>1.181</i>	18.0 <i>0.709</i>	60 <i>2.362</i>	5.5 <i>0.217</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	6.0 <i>0.236</i>	Pan Head M5
# UTRK2-RL-0200-AL	2	200 <i>7.874</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-0240-420	2	240 <i>9.449</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0240-CS	2	240 <i>9.449</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0300-AL	2	300 <i>11.811</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-0390-CS	2	390 <i>15.354</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0390-420	2	390 <i>15.354</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK2-RL-0400-AL	2	400 <i>15.748</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-0540-420	2	540 <i>21.260</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0540-CS	2	540 <i>21.260</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0600-AL	2	600 <i>23.622</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-0690-420	2	690 <i>27.165</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0690-CS	2	690 <i>27.165</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0800-AL	2	800 <i>31.496</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-0840-420	2	840 <i>33.071</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK2-RL-0840-CS	2	840 <i>33.071</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0990-420	2	990 <i>38.976</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-0990-CS	2	990 <i>38.976</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1000-AL	2	1000 <i>39.370</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-1140-420	2	1140 <i>44.882</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1140-CS	2	1140 <i>44.882</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1200-AL	2	1200 <i>47.244</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK2-RL-1290-420	2	1290 <i>50.787</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK2-RL-1290-CS	2	1290 <i>50.787</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1440-420	2	1440 <i>56.693</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1440-CS	2	1440 <i>56.693</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1590-420	2	1590 <i>62.598</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	420 Stainless Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1590-CS	2	1590 <i>62.598</i>	60 <i>2.362</i>	21.5 <i>0.846</i>	150 <i>5.906</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	1045 Carbon Steel	7.3 <i>0.287</i>	Pan Head M8
# UTRK2-RL-1600-AL	2	1600 <i>62.992</i>	45 <i>1.772</i>	22.0 <i>0.866</i>	100 <i>3.937</i>	8.8 <i>0.346</i>	Aluminum - Clear Anodised	Aluminum - Clear Anodised	7.0 <i>0.276</i>	Pan Head M8
# UTRK3-RL-0415-420	3	415 <i>16.339</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	420 Stainless Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-0415-CS	3	415 <i>16.339</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	1045 Carbon Steel	9.0 <i>0.354</i>	Pan Head M10

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utilitrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK3-RL-0665-420	3	665 <i>26.181</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	420 Stainless Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-0665-CS	3	665 <i>26.181</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	1045 Carbon Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-0915-CS	3	915 <i>36.024</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	1045 Carbon Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-0915-420	3	915 <i>36.024</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	420 Stainless Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-1165-420	3	1165 <i>45.866</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	420 Stainless Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-1165-CS	3	1165 <i>45.866</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	1045 Carbon Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-1415-420	3	1415 <i>55.709</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	420 Stainless Steel	9.0 <i>0.354</i>	Pan Head M10
# UTRK3-RL-1415-CS	3	1415 <i>55.709</i>	85 <i>3.346</i>	29.5 <i>1.161</i>	250 <i>9.843</i>	10.5 <i>0.413</i>	Aluminum - Clear Anodised	1045 Carbon Steel	9.0 <i>0.354</i>	Pan Head M10

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Utiltrak Guide Rails

Part Number	Rail Size	Overall Length (L +/- 2) mm	Width (S) mm	Height (H) mm	Hole Spacing (E) mm	Mounting Hole Diameter mm	Material (U Channel Track)	Material (Raceways)	Base Thickness (T) mm	Recommended Fastener
		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	
# UTRK3-RL-1665-CS	3	1665	85	29.5	250	10.5	Aluminum - Clear Anodised	1045 Carbon Steel	9.0	Pan Head M10
		<i>65.551</i>	<i>3.346</i>	<i>1.161</i>	<i>9.843</i>	<i>0.413</i>			<i>0.354</i>	
# UTRK3-RL-1665-420	3	1665	85	29.5	250	10.5	Aluminum - Clear Anodised	420 Stainless Steel	9.0	Pan Head M10
		<i>65.551</i>	<i>3.346</i>	<i>1.161</i>	<i>9.843</i>	<i>0.413</i>			<i>0.354</i>	

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
