



Socket Set Screws - Nylon Tipped - 304 Stainless Steel

10/4/2018

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Page 1 of 12

INFORMATION


Nylon tipped grub screws. Soft tip compresses into threads to become self locking. Helps to prevent shaft damage.

This catalogue to be read in conjunction with information at <http://www.minibearings.com.au//partslist/toolssetsfoldup/tools/all/1/>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
SS020M-0032-S4-NT	M2x0.4 (2mm Standard)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	304 Stainless	Socket	0.9 <i>0.035</i>	0.4 <i>0.016</i>
# SS020M-0042-S4-NT	M2x0.4 (2mm Standard)	4.2 <i>0.165</i>	5.0 <i>0.197</i>	0.8	304 Stainless	Socket		0.400 <i>0.016</i>
# SS020M-0052-S4-NT	M2x0.4 (2mm Standard)	5.2 <i>0.205</i>	6.0 <i>0.236</i>	0.8	304 Stainless	Socket		0.400 <i>0.016</i>
SS020M-0062-S4-NT	M2x0.4 (2mm Standard)	6.2 <i>0.244</i>	7.0 <i>0.276</i>	0.8	304 Stainless	Socket		0.400 <i>0.016</i>
SS022C-0032-S3-NT	2-56 UNC (2.184mm)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	304 Stainless Steel (18-8)	Socket		0.454 <i>0.018</i>
# SS022C-0032-S4-NT-SL	2-56 UNC (2.184mm)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	0.8	304 Stainless	Slotted		0.454 <i>0.018</i>
SS022C-0064-S3-NT	2-56 UNC (2.184mm)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	0.8	304 Stainless Steel (18-8)	Socket		0.454 <i>0.018</i>
# SS028C-0032-S3-NT	4-40 UNC (2.845mm)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	304 Stainless Steel (18-8)	Socket		0.635 <i>0.025</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 4 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
# SS028C-0032-S4-NT-SL	4-40 UNC (2.845mm)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	304 Stainless	Slotted		0.635 <i>0.025</i>
# SS028C-0064-S3-NT	4-40 UNC (2.845mm)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.6	304 Stainless Steel (18-8)	Socket		0.635 <i>0.025</i>
SS030M-0030-S3-NT	M3x0.5 (3mm Standard)	3.0 <i>0.118</i>	3.8 <i>0.150</i>	1.6	304 Stainless Steel (18-8)	Socket		0.500 <i>0.020</i>
SS030M-0032-S4-NT	M3x0.5 (3mm Standard)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	304 Stainless	Socket		0.500 <i>0.020</i>
SS030M-0040-S3-NT	M3x0.5 (3mm Standard)	4.0 <i>0.157</i>	4.8 <i>0.189</i>	1.6	304 Stainless Steel (18-8)	Socket		0.500 <i>0.020</i>
SS030M-0042-S4-NT	M3x0.5 (3mm Standard)	4.2 <i>0.165</i>	5.0 <i>0.197</i>	1.6	304 Stainless	Socket		0.500 <i>0.020</i>
# SS030M-0050-S3-NT	M3x0.5 (3mm Standard)	5.0 <i>0.197</i>	5.8 <i>0.228</i>	1.6	304 Stainless Steel (18-8)	Socket		0.500 <i>0.020</i>
SS030M-0052-S4-NT	M3x0.5 (3mm Standard)	5.2 <i>0.205</i>	6.0 <i>0.236</i>	1.6	304 Stainless	Socket		0.500 <i>0.020</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 5 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
SS030M-0052-S4-NT-SL	M3x0.5 (3mm Standard)	5.2 <i>0.205</i>	6.0 <i>0.236</i>	1.6	304 Stainless	Slotted		0.500 <i>0.020</i>
SS030M-0062-S4-NT	M3x0.5 (3mm Standard)	6.2 <i>0.244</i>	7.0 <i>0.276</i>	1.6	304 Stainless	Socket		0.500 <i>0.020</i>
# SS035C-0032-S3-NT	6-32 UNC (3.5mm)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS035C-0032-S4-NT-SL	6-32 UNC (3.5mm)	3.2 <i>0.126</i>	4.0 <i>0.157</i>	1.6	304 Stainless	Slotted		0.794 <i>0.031</i>
# SS035C-0048-S3-NT	6-32 UNC (3.5mm)	4.8 <i>0.189</i>	5.6 <i>0.220</i>	1.6	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
SS035C-0064-S3-NT	6-32 UNC (3.5mm)	6.4 <i>0.252</i>	7.1 <i>0.280</i>	1.6	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
SS040M-0038-S4-NT	M4x0.7 (4mm Standard)	3.8 <i>0.150</i>	5.0 <i>0.197</i>	2.4	304 Stainless	Socket		0.700 <i>0.028</i>
SS040M-0040-S3-NT	M4x0.7 (4mm Standard)	4.0 <i>0.157</i>	5.2 <i>0.205</i>	2.4	304 Stainless Steel (18-8)	Socket		0.700 <i>0.028</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 6 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
SS040M-0058-S4-NT	M4x0.7 (4mm Standard)	5.8 <i>0.228</i>	7.0 <i>0.276</i>	2.4	304 Stainless	Socket		0.700 <i>0.028</i>
# SS040M-0058-S4-NT-SL	M4x0.7 (4mm Standard)	5.8 <i>0.228</i>	7.0 <i>0.276</i>	2.4	304 Stainless	Slotted		0.700 <i>0.028</i>
SS040M-0060-S3-NT	M4x0.7 (4mm Standard)	6.0 <i>0.236</i>	7.2 <i>0.283</i>	2.4	304 Stainless Steel (18-8)	Socket		0.700 <i>0.028</i>
SS040M-0098-S4-NT	M4x0.7 (4mm Standard)	9.8 <i>0.386</i>	11.0 <i>0.433</i>	2.4	304 Stainless	Socket		0.700 <i>0.028</i>
SS040M-0100-S3-NT	M4x0.7 (4mm Standard)	10.0 <i>0.394</i>	11.2 <i>0.441</i>	2.4	304 Stainless Steel (18-8)	Socket		0.700 <i>0.028</i>
SS040M-0138-S4-NT	M4x0.7 (4mm Standard)	13.8 <i>0.543</i>	15.0 <i>0.591</i>	2.4	304 Stainless	Socket		0.700 <i>0.028</i>
# SS042C-0032-S3-NT	8-32 UNC (4.166mm)	3.2 <i>0.126</i>	4.4 <i>0.173</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS042C-0048-S4-NT-SL	8-32 UNC (4.166mm)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	304 Stainless	Slotted		0.794 <i>0.031</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 7 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
# SS042C-0048-S3-NT	8-32 UNC (4.166mm)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS042C-0064-S3-NT	8-32 UNC (4.166mm)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS042C-0095-S3-NT	8-32 UNC (4.166mm)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS048C-0048-S3-NT	10-24 UNC (4.762mm)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	304 Stainless Steel (18-8)	Socket		1.058 <i>0.042</i>
# SS048C-0048-S4-NT-SL	10-24 UNC (4.762mm)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	304 Stainless	Slotted		1.058 <i>0.042</i>
# SS048C-0095-S4-NT	10-24 UNC (4.762mm)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.4	304 Stainless	Socket		1.058 <i>0.042</i>
SS048F-0048-S3-NT	10-32 UNF (4.762mm)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS048F-0048-S4-NT-SL	10-32 UNF (4.762mm)	4.8 <i>0.189</i>	6.0 <i>0.236</i>	2.4	304 Stainless	Slotted		0.794 <i>0.031</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 8 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
# SS048F-0064-S3-NT	10-32 UNF (4.762mm)	6.4 <i>0.252</i>	7.5 <i>0.295</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS048F-0095-S3-NT	10-32 UNF (4.762mm)	9.5 <i>0.374</i>	10.7 <i>0.421</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS048F-0127-S3-NT	10-32 UNF (4.762mm)	12.7 <i>0.500</i>	13.9 <i>0.547</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
# SS048F-0191-S3-NT	10-32 UNF (4.762mm)	19.1 <i>0.752</i>	20.2 <i>0.795</i>	2.4	304 Stainless Steel (18-8)	Socket		0.794 <i>0.031</i>
SS050M-0058-S4-NT	M5x0.8 (5mm Standard)	5.8 <i>0.228</i>	7.0 <i>0.276</i>	2.4	304 Stainless	Socket		0.800 <i>0.031</i>
SS050M-0060-S3-NT	M5x0.8 (5mm Standard)	6.0 <i>0.236</i>	7.2 <i>0.283</i>	2.4	304 Stainless Steel (18-8)	Socket	2.5 <i>0.098</i>	0.800 <i>0.031</i>
SS050M-0098-S4-NT	M5x0.8 (5mm Standard)	9.8 <i>0.386</i>	11.0 <i>0.433</i>	2.4	304 Stainless	Socket		0.800 <i>0.031</i>
# SS050M-0098-S4-NT-SL	M5x0.8 (5mm Standard)	9.8 <i>0.386</i>	11.0 <i>0.433</i>	2.4	304 Stainless	Slotted		0.800 <i>0.031</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 9 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
SS050M-0100-S3-NT	M5x0.8 (5mm Standard)	10.0 <i>0.394</i>	11.2 <i>0.441</i>	2.4	304 Stainless Steel (18-8)	Socket		0.800 <i>0.031</i>
# SS050M-0138-S4-NT	M5x0.8 (5mm Standard)	13.8 <i>0.543</i>	15.0 <i>0.591</i>	2.4	304 Stainless	Socket		0.800 <i>0.031</i>
# SS050M-0198-S4-NT	M5x0.8 (5mm Standard)	19.8 <i>0.780</i>	21.0 <i>0.827</i>	2.4	304 Stainless	Socket		0.800 <i>0.031</i>
SS060M-0059-S4-NT	M6x1 (6mm Standard)	5.9 <i>0.232</i>	7.5 <i>0.295</i>	3.2	304 Stainless	Socket		1.000 <i>0.039</i>
# SS060M-0059-S4-NT-SL	M6x1 (6mm Standard)	5.9 <i>0.232</i>	7.5 <i>0.295</i>	3.2	304 Stainless	Slotted		1.000 <i>0.039</i>
SS060M-0060-S3-NT	M6x1 (6mm Standard)	6.0 <i>0.236</i>	7.6 <i>0.299</i>	3.2	304 Stainless Steel (18-8)	Socket	3.0 <i>0.118</i>	1.000 <i>0.039</i>
SS060M-0099-S4-NT	M6x1 (6mm Standard)	9.9 <i>0.390</i>	11.5 <i>0.453</i>	3.2	304 Stainless	Socket	3.0 <i>0.118</i>	1.000 <i>0.039</i>
# SS060M-0159-S4-NT	M6x1 (6mm Standard)	15.9 <i>0.626</i>	17.5 <i>0.689</i>	3.2	304 Stainless	Socket		1.000 <i>0.039</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 10 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (Tl) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
# SS060M-0249-S4-NT	M6x1 (6mm Standard)	24.9 <i>0.980</i>	26.5 <i>1.043</i>	3.2	304 Stainless	Socket		1.000 <i>0.039</i>
SS064C-0064-S3-NT	1/4-20 UNC (6.35mm)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.2	304 Stainless Steel (18-8)	Socket		1.270 <i>0.050</i>
# SS064C-0064-S4-NT-SL	1/4-20 UNC (6.35mm)	6.4 <i>0.252</i>	7.9 <i>0.311</i>	3.2	304 Stainless	Slotted		1.270 <i>0.050</i>
# SS064C-0095-S3-NT	1/4-20 UNC (6.35mm)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.2	304 Stainless Steel (18-8)	Socket		1.270 <i>0.050</i>
# SS064C-0127-S3-NT	1/4-20 UNC (6.35mm)	12.7 <i>0.500</i>	14.3 <i>0.563</i>	3.2	304 Stainless Steel (18-8)	Socket		1.270 <i>0.050</i>
# SS064F-0095-S3-NT	1/4-28 UNF (6.35mm)	9.5 <i>0.374</i>	11.1 <i>0.437</i>	3.2	304 Stainless Steel (18-8)	Socket		0.907 <i>0.036</i>
# SS079C-0095-S3-NT	5/16-18 UNC (7.938mm)	9.5 <i>0.374</i>	11.9 <i>0.469</i>	4.8	304 Stainless Steel (18-8)	Socket		1.411 <i>0.056</i>
# SS095C-0254-S3-NT	3/8-16 UNC (9.525mm)	25.4 <i>1.000</i>	27.8 <i>1.094</i>	4.8	304 Stainless Steel (18-8)	Socket		1.588 <i>0.063</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 11 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - 304 Stainless Steel

Part Number	Thread Size	Thread Length (TI) mm	Overall Length (L) mm	Tip Diameter (D)	Material	Drive Type	Drive Size mm	Pitch mm
		<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
SS100M-0121-S4-NT	M10x1.5 (10mm Standard)	12.1 <i>0.476</i>	14.5 <i>0.571</i>	4.8	304 Stainless	Socket		1.500 <i>0.059</i>
SS100M-0201-S4-NT	M10x1.5 (10mm Standard)	20.1 <i>0.791</i>	22.5 <i>0.886</i>	4.8	304 Stainless	Socket		1.500 <i>0.059</i>
SS100M-0301-S4-NT	M10x1.5 (10mm Standard)	30.1 <i>1.185</i>	32.5 <i>1.280</i>	4.8	304 Stainless	Socket		1.500 <i>0.059</i>

Indicates item not stocked at time of printing - Please enquire for lead time

Page 12 of 12

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

DISTRIBUTED BY

Distributed By:

