



Socket Set Screws - Nylon Tipped - Alloy Steel

10/4/2018

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Page 1 of 8

INFORMATION


Nylon tipped grub screws. Soft tip compresses into threads to become self locking. Helps to prevent shaft damage.

This catalogue to be read in conjunction with information at <http://www.minibearings.com.au//partslist/toolssetsfoldup/tools/all/1/>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - Alloy Steel

| Part Number | Thread Size | Thread Length (TL) | Overall Length (L) | Tip Diameter (D) | Material | Drive Type | Pitch mm |
|---------------------|-----------------------|---------------------|----------------------|------------------|-------------------|------------|-----------------------|
| | | mm | mm | | | | inches |
| # SS028C-0032-AS-NT | 4-40 UNC (2.845mm) | 3.2 <i>0.126</i> | 4.0 <i>0.157</i> | 1.59 | Black Oxide Steel | Socket | 0.635 <i>0.025</i> |
| SS028C-0048-AS-NT | 4-40 UNC (2.845mm) | 4.8 <i>0.189</i> | 5.6 <i>0.220</i> | 1.59 | Black Oxide Steel | Socket | 0.635 <i>0.025</i> |
| SS028C-0064-AS-NT | 4-40 UNC (2.845mm) | 6.4 <i>0.252</i> | 7.1 <i>0.280</i> | 1.59 | Black Oxide Steel | Socket | 0.635 <i>0.025</i> |
| # SS035C-0032-AS-NT | 6-32 UNC (3.5mm) | 3.2 <i>0.126</i> | 4.0 <i>0.157</i> | 1.59 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS035C-0048-AS-NT | 6-32 UNC (3.5mm) | 4.8 <i>0.189</i> | 5.6 <i>0.220</i> | 1.59 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS035C-0064-AS-NT | 6-32 UNC (3.5mm) | 6.4 <i>0.252</i> | 7.1 <i>0.280</i> | 1.59 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS035C-0095-AS-NT | 6-32 UNC (3.5mm) | 9.5 <i>0.374</i> | 10.3 <i>0.406</i> | 1.59 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| SS040M-0040-AS-NT | M4x0.7 (4mm Standard) | 4.0 <i>0.157</i> | 5.2 <i>0.205</i> | 2.4 | Black Oxide Steel | Socket | 0.700 <i>0.028</i> |
| # SS040M-0060-AS-NT | M4x0.7 (4mm Standard) | 6.0 <i>0.236</i> | 7.2 <i>0.283</i> | 2.4 | Black Oxide Steel | Socket | 0.700 <i>0.028</i> |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - Alloy Steel

| Part Number | Thread Size | Thread Length (TL) mm <i>inches</i> | Overall Length (L) mm <i>inches</i> | Tip Diameter (D) | Material | Drive Type | Pitch mm <i>inches</i> |
|---------------------|-----------------------|---|---|------------------|-------------------|------------|---------------------------|
| # SS040M-0080-AS-NT | M4x0.7 (4mm Standard) | 8.0 <i>0.315</i> | 9.2 <i>0.362</i> | 2.4 | Black Oxide Steel | Socket | 0.700 <i>0.028</i> |
| # SS042C-0032-AS-NT | 8-32 UNC (4.166mm) | 3.2 <i>0.126</i> | 4.4 <i>0.173</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS042C-0048-AS-NT | 8-32 UNC (4.166mm) | 4.8 <i>0.189</i> | 6.0 <i>0.236</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS042C-0064-AS-NT | 8-32 UNC (4.166mm) | 6.4 <i>0.252</i> | 7.5 <i>0.295</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS042C-0095-AS-NT | 8-32 UNC (4.166mm) | 9.5 <i>0.374</i> | 10.7 <i>0.421</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS042C-0127-AS-NT | 8-32 UNC (4.166mm) | 12.7 <i>0.500</i> | 13.9 <i>0.547</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS048C-0064-AS-NT | 10-24 UNC (4.762mm) | 6.4 <i>0.252</i> | 7.5 <i>0.295</i> | 2.38 | Black Oxide Steel | Socket | 1.058 <i>0.042</i> |
| # SS048F-0048-AS-NT | 10-32 UNF (4.762mm) | 4.8 <i>0.189</i> | 6.0 <i>0.236</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS048F-0064-AS-NT | 10-32 UNF (4.762mm) | 6.4 <i>0.252</i> | 7.5 <i>0.295</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS048F-0095-AS-NT | 10-32 UNF (4.762mm) | 9.5 <i>0.374</i> | 10.7 <i>0.421</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |

Indicates item not stocked at time of printing - Please enquire for lead time

Page 5 of 8

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - Alloy Steel

| Part Number | Thread Size | Thread Length (TL) mm <i>inches</i> | Overall Length (L) mm <i>inches</i> | Tip Diameter (D) | Material | Drive Type | Pitch mm <i>inches</i> |
|---------------------|---------------------|---|---|------------------|-------------------|------------|---------------------------|
| # SS048F-0127-AS-NT | 10-32 UNF (4.762mm) | 12.7 <i>0.500</i> | 13.9 <i>0.547</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS048F-0191-AS-NT | 10-32 UNF (4.762mm) | 19.1 <i>0.752</i> | 20.2 <i>0.795</i> | 2.38 | Black Oxide Steel | Socket | 0.794 <i>0.031</i> |
| # SS060M-0080-AS-NT | M6x1 (6mm Standard) | 8.0 <i>0.315</i> | 9.6 <i>0.378</i> | 3.2 | Black Oxide Steel | Socket | 1.000 <i>0.039</i> |
| # SS064C-0048-AS-NT | 1/4-20 UNC (6.35mm) | 4.8 <i>0.189</i> | 6.3 <i>0.248</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064C-0064-AS-NT | 1/4-20 UNC (6.35mm) | 6.4 <i>0.252</i> | 7.9 <i>0.311</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064C-0079-AS-NT | 1/4-20 UNC (6.35mm) | 7.9 <i>0.311</i> | 9.5 <i>0.374</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064C-0095-AS-NT | 1/4-20 UNC (6.35mm) | 9.5 <i>0.374</i> | 11.1 <i>0.437</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064C-0127-AS-NT | 1/4-20 UNC (6.35mm) | 12.7 <i>0.500</i> | 14.3 <i>0.563</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064C-0159-AS-NT | 1/4-20 UNC (6.35mm) | 15.9 <i>0.626</i> | 17.5 <i>0.689</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064C-0191-AS-NT | 1/4-20 UNC (6.35mm) | 19.1 <i>0.752</i> | 20.6 <i>0.811</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |

Indicates item not stocked at time of printing - Please enquire for lead time

Page 6 of 8

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - Alloy Steel

| Part Number | Thread Size | Thread Length (TI) mm <i>inches</i> | Overall Length (L) mm <i>inches</i> | Tip Diameter (D) | Material | Drive Type | Pitch mm <i>inches</i> |
|---------------------|---------------------------|---|---|------------------|-------------------|------------|---------------------------|
| # SS064C-0254-AS-NT | 1/4-20 UNC (6.35mm) | 25.4 <i>1.000</i> | 27.0 <i>1.063</i> | 3.18 | Black Oxide Steel | Socket | 1.270 <i>0.050</i> |
| # SS064F-0064-AS-NT | 1/4-28 UNF (6.35mm) | 6.4 <i>0.252</i> | 7.9 <i>0.311</i> | 3.18 | Black Oxide Steel | Socket | 0.907 <i>0.036</i> |
| # SS064F-0095-AS-NT | 1/4-28 UNF (6.35mm) | 9.5 <i>0.374</i> | 11.1 <i>0.437</i> | 3.18 | Black Oxide Steel | Socket | 0.907 <i>0.036</i> |
| # SS064F-0127-AS-NT | 1/4-28 UNF (6.35mm) | 12.7 <i>0.500</i> | 14.3 <i>0.563</i> | 3.18 | Black Oxide Steel | Socket | 0.907 <i>0.036</i> |
| # SS079C-0095-AS-NT | 5/16-18 UNC (7.938mm) | 9.5 <i>0.374</i> | 11.9 <i>0.469</i> | 4.76 | Black Oxide Steel | Socket | 1.411 <i>0.056</i> |
| # SS079C-0127-AS-NT | 5/16-18 UNC (7.938mm) | 12.7 <i>0.500</i> | 15.1 <i>0.594</i> | 4.76 | Black Oxide Steel | Socket | 1.411 <i>0.056</i> |
| # SS079C-0191-AS-NT | 5/16-18 UNC (7.938mm) | 19.1 <i>0.752</i> | 21.4 <i>0.843</i> | 4.76 | Black Oxide Steel | Socket | 1.411 <i>0.056</i> |
| # SS079C-0254-AS-NT | 5/16-18 UNC (7.938mm) | 25.4 <i>1.000</i> | 27.8 <i>1.094</i> | 4.76 | Black Oxide Steel | Socket | 1.411 <i>0.056</i> |
| # SS080M-0080-AS-NT | M8x1.25 (8mm Standard) | 8.0 <i>0.315</i> | 10.4 <i>0.409</i> | 0.00 | Black Oxide Steel | Socket | 1.250 <i>0.049</i> |

Indicates item not stocked at time of printing - Please enquire for lead time

Page 7 of 8

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Socket Set Screws - Nylon Tipped - Alloy Steel

| Part Number | Thread Size | Thread Length (TI) mm <i>inches</i> | Overall Length (L) mm <i>inches</i> | Tip Diameter (D) | Material | Drive Type | Pitch mm <i>inches</i> |
|---------------------|-------------------------|---|---|------------------|-------------------|------------|---------------------------|
| # SS095C-0095-AS-NT | 3/8-16 UNC (9.525mm) | 9.5 <i>0.374</i> | 11.9 <i>0.469</i> | 4.76 | Black Oxide Steel | Socket | 1.588 <i>0.063</i> |
| # SS095C-0127-AS-NT | 3/8-16 UNC (9.525mm) | 12.7 <i>0.500</i> | 15.1 <i>0.594</i> | 4.76 | Black Oxide Steel | Socket | 1.588 <i>0.063</i> |
| # SS095C-0254-AS-NT | 3/8-16 UNC (9.525mm) | 25.4 <i>1.000</i> | 27.8 <i>1.094</i> | 4.76 | Black Oxide Steel | Socket | 1.588 <i>0.063</i> |
| # SS127C-0191-AS-NT | 1/2-13 UNC (12.7mm) | 19.1 <i>0.752</i> | 22.2 <i>0.874</i> | 6.35 | Black Oxide Steel | Socket | 1.954 <i>0.077</i> |
| # SS127C-0254-AS-NT | 1/2-13 UNC (12.7mm) | 25.4 <i>1.000</i> | 28.6 <i>1.126</i> | 6.35 | Black Oxide Steel | Socket | 1.954 <i>0.077</i> |

Indicates item not stocked at time of printing - Please enquire for lead time

Page 8 of 8

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

DISTRIBUTED BY

Distributed By:

